ADELCU-EOL

Alarmline II Digital EN, spare end-of-line unit

General

Replacement end-of-line unit for use with the AlarmLine II Digital EN linear heat detection controller and AlarmLine II Digital EN linear heat detection cable.

Functional testing

Internally the unit features 4 switches, which can be used to simulate a fire or fault on each of the zones. There are two push-buttons, one for each zone, which simulate a fire by connecting the two cable cores when the button is pressed. Similarly there are two switches, which under normal conditions connect the end-of-line resistor across the cable, for each zone. However when the switch is changed, this create an open circuit which in turn raises a fault on the controller. Via these switches it is easy to functionally test the system.



Détails

- Quickly simulate a fault condition
- Quickly simulate an alarm condition
- Supplied with 2 IP67 rated cable glands
- Secure, weatherproof enclosure
- RoHS compliant, CE & EN54-28:2016 certified

ADELCU-EOL

Alarmline II Digital EN, spare end-of-line unit

Spécifications techniques

Électrique

Bornes	5 mm rising clamp

Caractéristiques physiques

Dimensions physiques	94 x 94 x 57 mm (W x H x D)

Environnement

Température de fonctionnement	-35 to +55°C
Indice de protection	IP66

Régulateur

Certification	CE, EN54-28

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 16 May 2025 - 12:10