AI2672

2000 Series Loop Powered Dual Indicator

General

The AI2672 is a 2000 series, addressable remote indicator. It is used to repeat an alarm condition signalled from one or more devices for which the alarm LEDs on the devices may be obscured or not visible in plain sight. The AI2672 is fully programmable when using a fire panel (CIE) supporting 2000 series addressable protocol.

Addressable and Loop Powered

The addressing on the AI2672 is done via easy to use, DIP switches, and allows the device to be programmed similar to other notification devices on the 2000 series loop. It can be freely controlled from the CIE and simply be assigned to duplicate the required detector (or other device) status.

Installation

The AI2672 is housed in a plastic enclosure suitable for surface mount assembly on commercial switch boxes. Two 10 mm LEDs are installed on either side of the body of the device to ensure clear visibility in all directions, allowing the AI2672 to be used for both ceiling mount as well as wall mount applications.



Détails

- Wide operating voltage
- Low current consumption
- Wall or ceiling mounted
- Low profile
- 360°, clearly visible, large LEDs

AI2672

2000 Series Loop Powered Dual Indicator

Spécifications techniques

Électrique

Tension de fonctionnement	20 to 30 VDC
Consommation de courant	0.3 mA (Quiescent) 2.3 mA (Alarm)

Caractéristiques physiques

Dimensions physiques	85 x 29 x 85 mm (W x H x L)
Poids net	65 g
Couleur	Blanc

Environnement

Température de fonctionnement	-10 to +50°C
Environnement	Intérieur
Indice de protection	IP50

Régulateur

Certification	CE

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 19 January 2026 - 10:45