AS2364W

2000 Series Loop Powered Sounder, Multi-Tone, Deep Base - (WHITE)

General

The AS2364W is a WHITE bodied, deep base addressable room sounder for fire alarm systems running 2000 series addressable fire protocol. Multiple tone selection and full CPD approval ensure conformance to local regulations.

The sounders operate over a 2-wire 2000 series loop and are loop powered i.e. no external power supply is required. They are compatible with automatic phased-start synchronisation controlled from the fire panel. The AS2364W has a IP65 enclosure.

Installation

Device cabling is done to the base and allows the sounder to be fitted and locked into position afterwards. A separate earth terminal is provided in the base for connecting the screen or functional earth when required.

Efficient and versatile

These sounders can be put into different operating modes depending on local requirements. It provides high sound output at a low current, thus reducing power standby requirements and overall system cost. They are supplied with high/low volume settings as standard, allowing final audio adjustments to be made during installation.

The sounder is tone selectable during installation. 32 tone settings are available.



Détails

- Loop powered
- High sound output with low current consumption
- Multiple tone selection
- Suitable for multiple stage evacuation with up to 3 pre-set tones
- Automatic synchronisation
- IP65 rated
- CPD certified

AS2364W

2000 Series Loop Powered Sounder, Multi-Tone, Deep Base - (WHITE)

Spécifications techniques

Général

Compatibilité	2000 Series systems
Méthode d'adressage	DIP Switches
Contrôle	Sound output
System support	Addressable systems

Électrique

Type de bloc d’alimentation	Alimenté en boucle
Consommation électrique	120 mW
Protection surtensions	<1.2 mA @ 24 VDC
Tension de fonctionnement	17 to 28 VDC
Tension de communication	5 to 9 V
Consommation de courant	310 µA @ 24 V (Quiescent) 5.1 mA @ 24 V (Sounder activated)
Taille du câble	0.28 to 2.5 mm²

Sirène

Niveau de sortie	< 97 dBA (±3 dB(A)) at 1 m @ 90º (tone and voltage dependent)
Level Adjustment (ajustement du niveau)	8 dB (Typical)
Fréquence	400 - 2850 Hz (Tone dependent)
Tonalités sélectionnables	32
Synchronisation	Supported

Caractéristiques physiques

Dimensions physiques	100 x 104 mm (Ø x H)
Poids net	250 g
Matériel	Polycarbonate haut impact

Environnement

Température de fonctionnement	-10 to +55°C
Température de stockage	-10 to +55°C
Humidité relative	5 to 95% noncondensing
Environnement	Intérieur
Indice de protection	IP65

Régulateur

Certification	EN54-3

Physical

Cable size	0.28 to 2.5 mm²

Produits compatibles

Catégorie	Référence	Description
Module de notification	AS36RIM	Sounder Beacon Rim With "Fire" Text (English)

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 6 May 2026 - 13:17