AS600FLASH

Flash module for AS 600 Series



Détails

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- 300 x 210 x 87 mm
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Installer friendly
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

AS600FLASH
Flash module for AS 600 Series

Spécifications techniques

Général

Groupe d'accessoires	Sirène
Type	Pièce de rechange

Spécifications du flash

Consommation de courant	110 mA
Sortie de la lumière	100,000 peak lumens
Fréquence du flash	60 flashes/minute

Électrique

Valeur de l'alimentation	10.5 to 13.8 VDC
Tension de fonctionnement	13 to 14.2 V
Consommation de courant	700 mA

Caractéristiques physiques

Dimensions physiques	300 x 210 x 87 mm
Poids net	3 kg
Matériel	Polycarbonate / Inox

Environnement

Température de fonctionnement	-25 to 55°C

Sounder

Sound output at 1 m	110 dB
Frequency	0.7 to 1.2 kHz

Beacon

Spike suppression network	Standard fitted

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 21 January 2026 - 19:51