AS620RF-RC

Remote control for AS620RF-TR-N, 868 Mhz

The AS620RF-RC is a two-way remote control with four programmable buttons to send easy remote commands to the transceiver module AS620RF-TR-N. Immediate visual feedback of the status will be provided by the 4 status LEDs, one for each output.

All the main functions of an alarm control panel can be assigned to the buttons, i.e. switching on, switching off, specific output activations, etc.

Up to 4 remote controls can be added to allow the end-user to operate his security system in a quick and easy way.

Détails

- Remote control for AS620-TR-N
- Two-way wireless communication
- Supplied with two different button graphics
- Up to 4 remote controls with single AS620RF-TR-N
- Status LEDs

AS620RF-RC

Remote control for AS620RF-TR-N, 868 Mhz

Spécifications techniques

Électrique

Tension de fonctionnement	3 VDC lithium battery, model CR2032

Caractéristiques physiques

Dimensions physiques	80 x 35 x 16 mm

General

Operating frequency	868 MHz
Wireless signal range	200 m
Compatability	AS620RF-TR-N

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2025 - 12:07