AS620RF-TR-N

Spare transceiver unit for AS620RF-N, 868 Mhz

The AS620RF-TR-N is a spare transceiver module with housing and compatible with the AS620RF-N wireless siren. The unit is intended for indoor installation. The transceiver is able to control up to 4 wireless sirens and to receive and manage all information coming from the memorized sirens.

The transceiver features inputs and outputs to interface with an alarm control panel, along with buttons, LEDs, and a display for programming and fault indication.

Optionally, up to 4 remote controls can be added to allow the end-user to operate additional outputs through his security system in a quick and easy way.



Détails

- Spare transceiver for AS620-RF-N
- Two-way wireless communication
- Plastic housing with tamper protection
- In- and outputs to be used in conjunction with any alarm control panel
- Two 7-segment displays for fault indication and programming

AS620RF-TR-N

Spare transceiver unit for AS620RF-N, 868 Mhz

Spécifications techniques

Électrique

Tension de fonctionnement	12 VDC
Consommation de courant	50 mA (maximum) 10 mA (nominal)

Caractéristiques physiques

Dimensions physiques	155 x 100 x 50 mm
Poids à l'expédition	165 g

Environnement

Température de fonctionnement	-10 to +50°C

General

Operating frequency	868 MHz
Maximum power output	10 mW
Wireless signal range	500 m
Compatability	AS620RF-N, AS620RF-RC

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 21 January 2026 - 19:51