AS964I

Apollo XP95 Loop Powered Open-Area Sounder (Red) With Isolator (55000-001)

General

The AS964I is a 950 series, intelligent loop powered open-area sounder in RED with a built in isolator. It is designed for use in indoor and outdoor open area applications. It supports 3 tones with two volume settings.

A locking mechanism is available to prevent unauthorized removal of the AS964I from its base.

Isolation and Maintenance

The AS964I sounder is supplied with an isolating base. A yellow LED on the base is illuminated if a loop short circuit is detected. All fault and abnormal conditions such as sounder failures are reported back to the panel for easy faultfinding.

Sounder Tone Support

That AS964I supports the following tones:

·Standard
·Slow Whoop (NEN2575)
·DIN (33404pt3)

Two volume settings are available in each tone variant.



Détails

- Self-test fault monitoring
- Multiple tones
- Alarm synchronisation
- Loop powered
- Including loop isolator

AS964I

Apollo XP95 Loop Powered Open-Area Sounder (Red) With Isolator (55000-001)

Spécifications techniques

Électrique

Tension de fonctionnement	17 to 28 VDC
Consommation de courant	Quiescent: <333 µA @ 24 VDC Switch on surge (< 1 s): <1.2 mA @ 24 VDC Alarm (Sounder only): 5 mA @ 24 VDC

Sirène

Niveau de sortie	100 dB(A) @ 90° (± 3dB(A))
Fréquence	Tone dependant

Environnement

Environnement	Intérieur
Indice de protection	IP65

Régulateur

Certification	EN54-17, EN54-3

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 February 2025 - 11:37