ASC366

Conventional Ceiling Mount VAD, Multi Tone, Shallow Base - Red Flash

General

The ASC366 is a RED, general purpose, ceiling mount, electronic sounder and beacon for fire alarm applications. It features a special base containing all wiring connections allowing for easy placement or removal of the device. With an EN54-23 approved coverage pattern of C-3-8.9 for the beacon, each ASC366 may be mounted up to 3m high and provide a 8.9m cylinder diameter coverage. A room size of 6.3 x 6.3m square room may therefore be covered with a single device.

Easy and Fast Installation

The ASx360 series alarm sounder/beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws these devices use TimeSaver™ bases from the 630 series detector lines. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The ASx360 series sounders provide high sound output at a low current, thus reducing power requirements and system cost. They are supplied with a volume control as standard, allowing final audio adjustments to be made during installation. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The ASx360 series beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Détails

- High sound output with Pulse Alert™ technology
- 32 Tones user selectable
- Automatic syncronisation
- Volume control and adjustable flash rate
- Anti-Tamper locking mechanism
- Shallow mouting base with wiring to the base
- Seperate sounder and beacon and control
- EN54:3 and EN54:23 approved, CPR Certified

ASC366

Conventional Ceiling Mount VAD, Multi Tone, Shallow Base - Red Flash

Spécifications techniques

Général

Surveillance de ligne	Polarised input

Électrique

Tension de fonctionnement	17 to 60 VDC
Consommation de courant	Sounder: 5.1 mA, Beacon: 20 mA @ 0.5 Hz / 40 mA @ 1 Hz

Sirène

Niveau de sortie	85 to 97 dB(A) @ 1 m (tone dependant) Continuous operation
Tonalités sélectionnables	32
Synchronisation	Automatic, Phased start

VAD

Couleur	Red
Évaluation	C-3-8.9
Couverture de sol	up to 40 m²
Fréquence du flash	0.5 Hz
Synchronisation	Supported

Caractéristiques physiques

Dimensions physiques	100 x 94 (Ø x D)
Poids net	215 g
Couleur	Rouge
Type de montage	Assemblage sur socle
Position de montage	Ceiling
Hauteur de montage	up to 3 m
Base de fixation	Shallow
Matériel	Polycarbonate haut impact
Texture	Smooth

Environnement

Température de fonctionnement	-25 to +70°C
Humidité relative	5 to 95%
Environnement	Intérieur
Indice de protection	IP21

Régulateur


Conformité	CE, REACH, RoHS 3, WEEE
Certification	EN54-23, EN54-3

Regulatory

Voluntary marks (all languages)	BOSEC

Produits compatibles

Catégorie	Référence	Description
Module de notification	ASC366W	Conventional Ceiling Mount VAD, Multi Tone, Shallow Base - Red Flash
Module de notification	ASC367	Conventional Ceiling Mount VAD, Multi Tone, Deep Base - Red Flash



KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 19 March 2026 - 13:34