ATS1125-B

Everon and Axon keypad with Mifare reader, Black

Simplified Icon-based user interface with a modern design

The Everon product family has a new addition - the ATS1125-B graphical LCD keypad. It ensures a safe and secure environment for users, whether they use codes or cards. With the ATS1125-B, users can access control panel functions using cards, PIN codes or even both. It offers easy operation to the end users with quick arm functionality, part set, and programmable function keys.
The ATS1125-B has a modern design, featuring a new user interface with icon-based and readable text on a large graphical LCD display, with system status, alarms, and access control functions. The contrast, intensity of the display and key lights are adjustable via the keypad, along with the volume level of the built-in buzzer. The user can easily navigate through the programming, operational features and additional function keys using the navigation keys.

Built-in secure card reader

The ATS1125-B has a built-in Mifare Desfire EV1/EV2/EV3 card reader. In secure mode, card data is encrypted from the card to the keypad and from the keypad to the Everon control panel.
The ATS1125-B can be used for arming/disarming using the PIN code, the card or a combination of the two for higher security needs. It works with the multiple card badging solutions available in the Everon product family.
Alarm system activation: a user can turn on the alarm system by badging their card three times within a 10-second interval.
Door access control: doors can be programmed for specific behaviors based on badging with the card. For example, with a single badge scan, granting seamless entry and exit without requiring a card, and a triple badge scan will promptly re-lock the door, providing enhanced convenience for the end user.

LED indication

Three status LEDs will continuously update the user on main conditions, faults, access control and alarms.
There is a green (power, battery LED), yellow (fault LED) and a multi-color LED bar for blue (access LED) and red (alarm LED).
The ATS1125-B LEDs are a good complement to the large graphical LCD display that shows icons to guide the end user.

Mounting

The ATS1125-B can be installed using the mounting points in the backplate which also provide easy cable entry to connect the panel to the removable bus connector.
A big advantage of the back plate of the ATS1125-B is that the pattern fits round standard flush-mounted junction boxes with a 60-mm diameter, such as U40 or 502E.
This allows for a neat and stylish installation without extra complications. The hinges and the door are removable to make the installation as customized as possible.



Détails

- New design with a simplified icon-based user interface
- Large graphical LCD display
- Removable hinges for the lid (lid as an accessory)
- Possibility to add a custom logo to the display
- User-adjustable LCD, buzzer and key lights
- Built-in secure Mifare Desfire EV1/EV2/EV3 reader
- Supports secure Mifare (secure mode) or Mifare 4 or 7 byte CSN/UID (unsecure mode)
- Use secure ATS145x series cards or custom cards (excl. ATS1458)
- 3 programmable function keys (F+Key)

ATS1125-B

Everon and Axon keypad with Mifare reader, Black

Spécifications techniques

Général

Interface utilisateur	4-line graphical LCD
Gamme de produits	Axon, Everon
LED d'état	3
Lecteur intégré	Sécuriser MIFARE

Système

Touches de fonction	3
Types de cartes pris en charge	MIFARE® Classic UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Type d'adressage	Software Addressing
Type de câble pris en charge	WCAT 52/54 or equivalent

Communication

Type de communication	Câblés
Distance de lecture	Up to 3 cm

Entrées / sorties

Entrées	1
Type d'entrée	Request to Exit (NO)
Sorties	1
Type de sortie	Open collector, 13.7 V max. at 50 mA max.

Électrique

Tension de fonctionnement	8.7 to 15.1 VDC, 12 VDC nom.
Type de bloc d’alimentation	12 VDC
Consommation de courant	25 mA at 12 VDC normal operation 115 mA at 12 VDC max.

Caractéristiques physiques

Dimensions physiques	97 x 155 x 25 mm
Poids net	230 g
Couleur	Noir
Types de format	Vertical
Couvercle	Flip Cover
Type de montage	Montage en surface
Matériel	Plastique ABS

Environnement

Protégé contre le vandalisme	Non
Température de fonctionnement	-10 to +55°C
Humidité relative	0 to 95% noncondensing
Environnement	Intérieur
Indice de protection	IP30

Régulateur

EN50131 Grade	Grade 3
Conformité	CE, RoHS
Certification	EN50131 Grade 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Produits compatibles

Catégorie	Référence	Description
Accessoires	ATS1125-B-LID	

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 11 June 2026 - 17:56