

ATS1135-EL

Advisor Advanced residential keypad without display lens

ATS-LENS-100

To integrate your own company logo, the ATS1135-EL is designed in conjunction with the separately available ATS-LENS-100 LCD display covers.

The ATS-LENS-100 LCD display covers are suitable for printing a company logo and can be used in combination with the ATS1135-EL.

Simplified user interface

The ATS1135 is a new addition to the Advisor Advanced product family. The existing range of keypads and card readers are available and can be used in different environments, in and out-door. The ATS1135 was developed for all generations by a simplified end user operation: quick arm functionality, 2 levels of partset, programmable function keys.

Stylish design

The ATS1135 has a modern stylish design and has a clearly readable text on a large 2 x 16 characters LCD for displaying system programming, alarm and access control functions. The contrast and intensity of the display is adjustable via the keypad as well as the volume level of the built-in buzzer. Four arrow keys will navigate the user easily through the programming and operational features and 4 additional fixed functions keys will complete this user-friendly interface next to the 3 programmable function keys A,B &C.

Built-in card reader

The ATS1135 has a built in smart card reader. The ATS1135 can be used for arming/disarming using either the PIN or the card or a combination of the two for higher security needs. It is suitable for using the multiple card badging techniques which are available for the Advisor Advanced product family. A user can set the system in the evenings by badging his card three times within 10 seconds interval. Another application could be for doors which can be programmed so that badging once unlocks the door to allow people in and out without card, and badging three times re-locks the door.

LED Indication

Four status LED's will continuously update the user on mains condition, faults, access control and alarms.

Green - Power LED is on when the control panel is powered by the AC supply.

Yellow - Fault LED illuminates to indicate detection of a system fault.

Blue - Access LED flashes when access to an area assigned to the RAS is granted.

Red - Alarm LED illuminates when there is a system tamper or an area assigned to the RAS is in alarm state.

The Arming Station can display the status of an area or complete system via the status indication LED in between the navigation keys. When Green the area or system is disarmed, when Red the system is an armed or part armed state.



Détails

- Used in combination with ATS-LENS-100
- Stylish design
- Simplified end user operation
- Large 2 x 16 characters LCD
- User adjustable LCD contrast
- User adjustable buzzer
- Built-in smart card proximity reader
- Compatible with all Advisor Advanced control panels
- Clear system status indication
- 3 programmable function keys

Mounting

The ATS1135 can be mounted by using the mounting points in the backplate which also provides easy cable entry to connect the panel to the removable bus connector.

A backplate (ATS1135BPL) is available which can be used to cover the dimensions of a legacy keypad when updating an installation to the Advisor Advanced system.

ATS1135-EL

Advisor Advanced residential keypad without display lens

Spécifications techniques

Général

Interface utilisateur	2 x 16 Caract. LCD, Touch Buttons
Gamme de produits	Advisor Advanced
LED d'état	2
Lecteur intégré	Proximité

Système

Touches de fonction	3
Type d'adressage	DIP Switches
Type de câble pris en charge	WCAT 52/54 or equivalent

Communication

Type de communication	Câblés
-----------------------	--------

Entrées / sorties

Entrées	1
Type d'entrée	Request to Exit
Sorties	1
Type de sortie	Open collector, 15 V max. at 50 mA max.

Électrique

Tension de fonctionnement	8.5 to 14 VDC
Type de bloc d'alimentation	VDC
Consommation de courant	35 mA normal operation 155 mA max.

Caractéristiques physiques

Dimensions physiques	200 x 90 x 24 mm
Poids net	350 g
Couleur	Blanc
Types de format	Horizontal
Type de montage	Montage en surface

Environnement

Température de fonctionnement	-10 to +55°C
Humidité relative	0 to 95% noncondensing
Environnement	Intérieur
Indice de protection	IP30

Régulateur

EN50131 Grade	Grade 3
Conformité	CE, RoHS



En tant que société d'innovation, Carrier Fire & Security se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 5 May 2023 - 10:26