ATS1181

Secure Mifare DesFire EV1/EV2 card reader with PIN, output and RTE input in slim design

Product overview

The ATS MIFARE DESFire EV1/EV2 readers connect directly to the control panel or 4 door controller using the ATS databus. Communication to Axon and Advisor Advanced control panels is AES encrypted, providing data to be securely communicated from the card to the processing unit. The readers are configured through locally through keypad and control panel menu or addressed through the ATS1482 addressing card. Select secure cards from the ATS145x secure card series.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.
The ATS Mifare Desfire EV1 readers are designed to transfer card data is a secure and reliable way in various environments. The card data is by default secured by an Interlogix own security key, but can be changed easily in Axon or Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

Communication

The reader communicates over the ATS LAN databus to Axon or Advisor control panels and 4 door controllers. When connected to an Axon or Advisor Advanced control panels, the data between reader and control panel is AES encrypted, securing the data from the card or the PIN code until being processed.

Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 ratings. Readers can be installed directly on to a metal surface without any insulation.



Détails

- Secure ATS Mifare DESFire EV1/EV2 reader with PIN keypad
- Supports Secure Mifare (secure mode) or Mifare 4 or 7 byte CSN/UID (Unsecure mode)
- Use secure ATS145x series cards or customer cards
- Secure communication using AES-128 bit encryption between reader and Axon / Advisor Advanced / CDC4 control panel
- Robust molded plastic housing in slim design
- Indoor or outdoor mounting
- ATS bus interface
- Request To Exit input
- Open Collector Output (door open)
- Supported as of Advisor Advanced MR4.2 and Axon MR1.0

ATS1181

Secure Mifare DesFire EV1/EV2 card reader with PIN, output and RTE input in slim design

Spécifications techniques

Système

Distance de lecture	Secure: max 2 cm Unsecure: max 5 cm
Distance max. entre le lecteur et la centrale	1500 m
CSN (numéro de série carte)	Oui
Modèle de données personnalisé	Oui
Types de cartes pris en charge	Mifare Classic 7 Byte UID, MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Type d'adressage	Card Addressing
Nbre de LED	3

Technologie

Type de lecteur	Smart Card
Fréquence de transmission du fonctionnement du lecteur	13.56 MHz
Technologie supportée 13,56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (custom data), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data)
Type Mifare	ISO14443A
Nbre d'octets Mifare CSN	4 Bytes (non-unique), 4 Byte (S50), 7 Bytes (S50), 7 Byte (S70)

Interface et connexions

Interface	ATS RS-485
Type de connecteur	Queue cochon
Longueur de la queue de cochon	2 m

Entrées / sorties

Entrées	Request to exit
Sorties	1 Open Collector (10 mA)

Type d'autoprotection

Levier d'arrêt inviolable	Oui

Opération

Code PIN clavier	Oui
Longueur du code PIN	Defined by control panel

Électrique

Tension de fonctionnement	10.8 to 30 VDC
Consommation de courant	50 mA @ 13.8 VDC normal 80 mA @ 13.8 VDC max.

Caractéristiques physiques

Dimensions physiques	140 x 44 x 20 mm
Poids net	240 g
Poids à l'expédition	275 g
Couleur	Noir
Matériel	Plastique
Types de format	Slimline
Type de montage	Montage en surface

Environnement

Température de fonctionnement	-40 to +55°C
Température de stockage	-40 to +55°C
Environnement	Intérieur, Extérieur
Indice de protection	IP67 IK-09

Régulateur

Conformité	CE
Certification	VdS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 15:13