ATS1475X10

Carte de proximité ATS Hitag II

Product Overview

These cards are to be used on ATS readers. The cards are unprogrammed and have the number printed for easier administration. Both the smart ship and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.



Détails

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- 4 memory areas for credit applications
- Packed by 10

ATS1475X10

Carte de proximité ATS Hitag II

Spécifications techniques

Système

Distance de lecture	0 to 60 cm
Modèle de données personnalisé	Non
Types de lecteurs	Lecteur de proximité ATS

Technologie

Type d'identifiant	Proximité
Fréquence de fonctionnement des identifiants	125 KHz
Technologie supportée 125 kHz	HiTag 2

Impression

Impression directe recto	Oui

Informations de commande

Quantité minimum par commande	1
Cartes / jetons (par lot)	100

Caractéristiques physiques

Matériel	Chlorure de polyvinyle (PVC)
Types de format	CR80 (Crédit)
Dimensions physiques	86 x 54 mm
Couleur	Blanc

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:24