ATS1495

(10-pack) ISO Secure MF+HT2

Product overview

The ISO card in white color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV2 encryption. It can be used in secure mode with ATS118x range readers and ATS1136 keypad.
When used on other Mifare Readers the standard Mifare 7-byte CSN is provided instead of the secure card data.
In addition the card provides for Hitag2 card serial number as supported by ATS119x reader range and ATS111x and ATS1135 keypads to allow simultaneous use of both technologies while migrating from old to new secure technologies.



Détails

- Attractive designed keyfob in ISO card model
- Card data secured by AES encryption
- Mifare Desfire EV2 encrypted application
- Hitag2 Card Serial Number

ATS1495
(10-pack) ISO Secure MF+HT2

Spécifications techniques

Système

Distance de lecture	MiFare: Secure mode: between 1 - 5 cm Unsecure mode: between 2-5 cm Hitag2: Up to 30 cm Distance may vary based on reader
Modèle de données personnalisé	Non
Capacité mémoire	2K
Types de lecteurs	ATS ATS118x Secure Readers

Technologie

Type d'identifiant	Proximité, Carte à puce
Fréquence de fonctionnement des identifiants	125 KHz, 13.56 MHz
Technologie supportée 13,56 MHz	MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN)
Technologie supportée 125 kHz	HiTag 2

Impression

Impression directe recto	Non

Informations de commande

Quantité minimum par commande	1
Cartes / jetons (par lot)	10

Caractéristiques physiques

Matériel	Chlorure de polyvinyle (PVC)
Types de format	CR80 (Crédit)
Dimensions physiques	86 x 54 x 9 mm
Poids net	66 g
Poids à l'expédition	67
Couleur	Blanc
Étiquette de carte	Serial number

Environnement

Température de fonctionnement	-10 to +50°C
Indice de protection	IP68

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:24