ATS1521N

Two Way Audio Smart Satellite

Addressable microphone and speaker module

The ATS1521N two-way audio satellite is an audio device that is used for audio alarm verification. Depending on the control panel variant and firmware, there can be up to 32x ATS1521N satellites installed in the protected premises and connected to one Advisor Advanced panel with the ATS1520 two-way audio module and ATS7700 PSTN module installed.

The ATS1521N allows up to 3x ATS1522N slave audio satellites to be wired in. Any mix of maximum four ATS1521N and ATS1522N is allowed in one chain.



Détails

- Embedded speaker and microphone
- Addressable
- Supervised LAN connection to panel
- Audio connection to ATS1520
- Can be installed at 100m from ATS1520
- Housing tamper
- Speaker and microphone volume adjustment via potentiometers
- Speaker LED function
- Max 32 devices depending on Advisor Advanced panel variant
- Allows up to 3x ATS1522N slave satellites

ATS1521N
Two Way Audio Smart Satellite

Spécifications techniques

Général

Gamme de produits	Advisor Advanced

Réseau

Type de communicateur	Voix / audio

Audio

Microphone sensitivity range	10 m
Minimum sound level @ 10 m	55 dB

Électrique

Tension de fonctionnement	9 to 14 VDC, 12 VDC nominal
Consommation de courant	10 mA, standby 35 mA max.

Caractéristiques physiques

Dimensions physiques	157 x 91 x 34 mm
Poids net	201 g

Environnement

Température de fonctionnement	-10 to +55°C
Humidité relative	95% noncondensing

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:25