ATS1522N

Two Way Audio Slave Satellite

Slave microphone and speaker module

The ATS1522N two-way audio slave satellite is an auxiliary audio device for the addressable ATS1521N two-way audio satellite, used for audio alarm verification. Depending on the control panel variant and firmware, there can be up to 32x ATS1521N satellites installed in the protected premises and connected to one Advisor Advanced panel with the ATS1520 two-way audio Module and ATS7700 PSTN module installed.

There can be up to 3x ATS1522N slave satellites wired to the ATS1521N two-way audio satellite. Or a mix of maximum four ATS1521N and ATS1522N is allowed in one chain.



Détails

- Embedded speaker and microphone
- Audio connection to ATS1521N
- Housing tamper
- Speaker and microphone volume adjustment via potentiometers
- Speaker LED function
- Up to 3x ATS1522N slave satellites can be wired to the ATS1521N

ATS1522N
Two Way Audio Slave Satellite

Spécifications techniques

Général

Gamme de produits	Advisor Advanced

Réseau

Type de communicateur	Voix / audio

Audio

Microphone sensitivity range	10 m
Minimum sound level @ 10 m	55 dB

Caractéristiques physiques

Dimensions physiques	157 x 91 x 34 mm
Poids net	201 g

Environnement

Température de fonctionnement	-10 to +55°C
Humidité relative	95% noncondensing

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:25