BS131N

Battery, 12 V, 18 Ah

Product overview

Sealed Lead Acid battery 12 V / 18 Ah with MS bolt & nuts terminal type.



Détails

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS131N
Battery, 12 V, 18 Ah

Spécifications techniques

Général

Type de produit	Batterie plomb-acide scellée

Caractéristiques électriques

Voltage nominal	12 V
Capacité nominale	18 Ah
Résistance Interne approx	10 mOhm

Charge / décharge

Vitesse radio maximum	13.8 VDC at +20°C
Vitesse radio maximum	5.4 A
Clients filaire maximum	90 A

Température

Température de chargement	0 to +40°C
Température de décharge	-15 to +50°C

Caractéristiques physiques

Dimensions physiques	181 x 76 x 167 mm
Poids net	6.283 kg
Poids à l'expédition	6.283 kg
Matériel	ABS
Type de terminal	MS bolt & nuts

Environnement

Retardant incendie	Non
Température de fonctionnement	+0 to +40°C
Température de stockage	-15 to +50°C

Régulateur

Conformité	CE, RoHS 2, WEEE
Certification	VdS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 21 August 2026 - 17:50