CRR

Wall-mounted radio link alarm interface module

Product overview

The CRR Wall-Mounted Radio Link Alarm Interface Module allows you to transmit a fire alarm from radio linked alarm devices to a control panel, a remote transmitter, a sounder, a beacon, etc. When a radio linked device is in alarm, it sends the information to the radio link alarm interface module, which changes its state, transmitting the alarm information to the intrusion control panel or other device.



Détails

- Ease of installation
- Discrete design
- Up to 10 wireless Calypso smoke sensors connected

CRR

Wall-mounted radio link alarm interface module

Spécifications techniques

Général

Type	Fumée
Sirène intégrée	Non
LED d'état	Oui

Filaire / sans fil

Filaire / sans fil	Câblés

Électrique

Tension de fonctionnement	9 to 15 V
Type de bloc d’alimentation	12 VDC
Consommation électrique	0.1 mA at 12 VDC
Consommation de courant	25 mA

Caractéristiques physiques

Dimensions physiques	83 x 83 x 46 mm
Couleur	Rouge
Matériel	ABS

Environnement

Température de fonctionnement	-10 to 55°C
Environnement	Intérieur

Régulateur

Conformité	CE
Certification	EN14604

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 15 October 2024 - 14:08