DB952IAS

950 Series Integrated Base Sounder With Isolator

General

The DB952IAS is a range of integrated, self monitoring base sounders with integral short-circuit isolator for use on Series 950 and Series 990 systems. They incorporate a base into which a series 950 or 990 detector, or beacon can be fitted. It may also be used with a red (AS952CAP-R) or white (AS952CAP-W) cap for stand-alone use.



Tones

The DB952IAS sounders support multiple tones. A low tone range is useful in areas such as hospitals where a fire alert is initially intended to warn staff only. The sounder may be set to the high range for general use.

In addition to the standard tones in the DB952IAS, a slow whoop tone to Dutch standard NEN2575 is available in the DB952IAS-NEN, as well as a German standard DIN tone version in the DB952IAS-DIN.

Syncronisation

Synchronisation of tones ensures the integrity of the signal—tones from different sounders do not merge into one signal that could be mistaken for a different tone. DB952IAS sounders are synchronised with each other in both ‘alert’ and ‘evacuate’ modes.

Self Test

The acoustic self-test means that the sounder listens to itself when it is switched on. If no sound is detected a fault signal is transmitted when the sounder is polled.

The same self-test feature may also be used during commissioning or periodical maintenance testing. The sounder may simply be activated for at least 5 seconds and the control panel checked for a fault signal. If none is received, the sounder is working properly.

Détails

- Two tone ranges 55 to 75 dB and 75 to 91 dB
- Synchronisation of ‘alert’ and ‘evacuate’ tones
- Individual sounder addressing
- Available with built-in isolator
- Acoustic self-test
- Slow whoop option available

DB952IAS

950 Series Integrated Base Sounder With Isolator

Spécifications techniques

Électrique

Tension de fonctionnement	17 to 28 VDC 5 to 9 V (Protocol pulses)
Consommation de courant	5 mA @ 24 V (Sounder operated 75 - 91dB) 5 mA @ 24 V (Sounder operated 50 - 75 dB) 1.2 mA @ 24 V (Switch-on surge, <1 s) 200 µA @ 24 V (Quiescent)

Environnement

Température de fonctionnement	-20 to +60°C
Relative humidity	0 to 95% noncondensing
Environnement	Intérieur
IP rating	IP21D

Régulateur

Certification	EN54-17, EN54-3

Sound output

Maximum at 90°	91 dB(A)
Maximum to EN54	83 dB(A)
Sound pressure level	Tone dependent

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 6 October 2026 - 14:38