DC101S60

DC101 WITH 6 METER CABLE

DC101-Series

The DC101-Series surface mount magnetic contacts are designed for use in installations where a small, sealed unit is required. The reed switch is totally encapsulated in an exclusive polyurethane potting compound preventing moisture from entering the switch and causing false alarms.

Easy installation

The 16 mm standard gap distance allows for fast, easy installation and prevents false alarms from loose fitting doors. Recessed mounting holes make for clean-looking installations.

High Quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



Détails

- Convenient surface mounting
- Standard 2 m wire length
- Tamper loop provided
- Neat and tidy design

DC101S60

DC101 WITH 6 METER CABLE

Spécifications techniques

Général

Type d'application	Montage en surface
Type de contact	NC
Connectivité	4 wires, 6 m

Filaire / sans fil


Filaire / sans fil	Câblés
Déficit de fonctionnement	15 mm (max.)

Caractéristiques physiques

Dimensions physiques	50 x 9 x 9 mm

Régulateur

EN50131 Grade	Grade 2



En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 13 August 2026 - 11:05