DD1012PI-N

12 m, Dual Technology, 9 curtains, pet immune, digital pyro

Patented range gated radar technology

Motion sensors of the DD1000 Series incorporate a patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.
The radar operates on 5.8GHz frequency and will not interfere with any WiFi networks.
The DD1012PI-N motion sensor incorporates a new digital pyro for an improved signal quality and a better immunity to electrical interferences.

PIR technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.
Within our DD1012 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.
The DD1012PI is designed to be immune for pets up to 18 kg of weight (about 35 cm of height).

Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage. But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

Other members of the family

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity.
The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.



Détails

- Patented selectable range gated radar technology clearly defining the radar detection border
- PIR technology with patented mirror curtain optics
- Pet Immunity up to 18 kg (ca. 35 cm height)
- Intelligent alarm decision based on signal classification of the PIR and radar alarm
- Automatic continuous self diagnostics on all technologies
- Green mode : option to switch off the radar technology when the security system is not armed
- Holding several security approvals including EN Grade II
- Incorporates a new digital pyro that detects the temperature fluctuations with high degree of precision

DD1012PI-N

12 m, Dual Technology, 9 curtains, pet immune, digital pyro

Spécifications techniques

Général

Technologie	Dual
Type d'application	Fixation murale
Anti-masquage	Non
Insensible aux animaux	Oui
Caméra	Non
Kit levier d’arrêt anti-ouverture	ST400
Temps mise en route du détecteur	60 s

Détection

Plage de détection maximale	12 m
Sélection de la plage de détection	4, 6, 9, or 12 m selectable via dip switches
Nbre de rideaux	9
Couverture (champ de vision)	78°
Hyperfréquence (nom.)	5.8 GHz
Sortie Max. d'onde (à 1m)	0.003 µW/cm²
Protection sous-jacente	Oui
Plage de vitesse cible	0.2 to 3.0 m/s
Mémoire d'alarme	Oui
Durée de l'alarme	3 sec
Immunité d’ondulation crête à crête	2 V (at 12 VDC)

Filaire / sans fil

Filaire / sans fil	Câblés

Entrées / sorties

Caractéristique du relais d’alarme	NC, 80 mA 30 VDC, Form A
Caractéristique du relais d’alarme	NC, 80 mA 30 VDC, Form A
Configuration du relais	Multiple EOL values
Lignes de commande à distance	Day/Night, Walk test

Électrique

Tension de fonctionnement	9 to 15 VDC (12 V nominal)
Type de bloc d’alimentation	12 VDC
Consommation de courant	8 mA nominal

Caractéristiques physiques


Dimensions physiques	126 x 63 x 50 mm
Poids net	120 g
Couleur	Blanc
Hauteur de montage	1.8 to 3 m

Environnement

Température de fonctionnement	-10 to 55°C
Humidité relative	95% max., noncondensing
Environnement	Intérieur
Indice de protection	IP30 IK04

Régulateur

EN50131 Grade	Grade 2



En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 15:15