DD666-D

20 m ceiling mount Dual motion sensor, Germany

18 curtains of detection

The DD600 series complement the successful EV600 series PIRs with dual technology motion sensors. The 18 curtains offer a maximum detection capability, including full under crawl detection, throughout a protected area of up to 20m in diameter.

The unique mirror optics technology is a gliding focus, which creates continuous curtains that never loses track of the intruder.

4D signal processing

4D signal processing makes an effective discrimination between intruder and false alarm signals. Recognizing the diversity in security applications, the DD600 series features both 4D signal processing and Bi-curtain processing for the harsher environments.

The combination of mirror optics with 4D signal processing not only provides better detection but also increased stability and rejection of false alarms.

Range Controlled Radar

The DD600 sensors incorporate a unique radar technology that is range controlled and operates on 5.8GHz frequency. The range control means that no nuisance alarms are generated for movements beyond the detection pattern.

Flush Mounting

The EV600 and DD600 motion sensors can be flush mounted with the optional accessory 360FM. The 360FM ensures a neat integration in the ceiling, making only the top part of the sensor visible.



Détails

- Dual motion sensor
- Step & Gliding Focus Multi Curtain mirror optic
- Range controlled radar on 5.8 GHz
- Plug-in electronics
- Sealed optics
- 4D processing for reduced nuisance alarms
- Selectable coverage pattern using mirror masks
- Additional bi-curtain processing for harsh environment
- No adjustment required for different mounting heights
- EN50131-2-4 Grade 2 certified
- Several European approvals

DD666-D

20 m ceiling mount Dual motion sensor, Germany

Spécifications techniques

Général

Technologie	Dual
Type d'application	Montage au plafond
Anti-masquage	Non
Insensible aux animaux	Non
Caméra	Non
Kit levier d’arrêt anti-ouverture	ST400 (optional)

Détection

Plage de détection maximale	20 m
Portée de détection	20 m
Nbre de rideaux	18
Couverture (champ de vision)	360°
Hyperfréquence (nom.)	5.8 GHz
Sortie Max. d'onde (à 1m)	0.003 µW/cm²
Protection sous-jacente	Oui
Plage de vitesse cible	0.2 to 3.0 m/s
Mémoire d'alarme	Oui
Durée de l'alarme	3 sec
Immunité d’ondulation crête à crête	2 V (at 12 VDC)

Filaire / sans fil

Filaire / sans fil	Câblés

Entrées / sorties

Caractéristique du relais d’alarme	NC, 80 mA 30 VDC, Form C
Caractéristique du relais d’alarme	NC, 80 mA 30 VDC, Form C
Lignes de commande à distance	Day/Night, Walk test

Électrique

Tension de fonctionnement	9 to 15 VDC
Type de bloc d’alimentation	12 VDC
Consommation de courant	12 mA

Caractéristiques physiques

Dimensions physiques	138 x 92 mm
Couleur	Blanc
Hauteur de montage	2.5 to 5 m

Environnement

Température de fonctionnement	-10 to +55°C
Humidité relative	95%
Environnement	Intérieur

Régulateur

EN50131 Grade	Grade 2
Certification	VdS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 15:16