DMN960IE

990 Series Manual Call Point Waterproof With Isolator - Red (Surface Mount)

General

The DMN960IE is an addressable, waterproof manual call point designed for use outdoors and in places where moisture and dirt may be a problem. It is compliant with EN54-11/17 and can be used with the 900 series device range on Aritech addressable panels. It is shipped with an easily resettable element rather than a break glass.

Operating Principles

All 960 series call points are addressed at the commissioning stage by means of a seven-segment DIL switch. The DMN960IE incorporates a short circuit isolator that ensures its operation in the event of a short circuit fault on the loop.

A single bi-coloured alarm LED is provided on the call point. The LED may be controlled independently of the call point from the FP1200/2000 fire panel. The LED is illuminated RED when the call point has been activated, or AMBER/YELLOW to indicate a short circuit.

Installation and Operation

The DMN960IE helps reduce installation time as all the initial installation cabling is wired to a terminal block that fits neatly in the back of the call point.

Once activated the call point can be easily reset by using the supplied test key and simply pushing the front cover up.

Approvals

All manual call points in the 960 series have been tested and approved by LPCB and a number of other approval authorities.

EN54-11 and EN54-17 approved
CE and CPD certified



Détails

- IP67 waterproof
- Tamper resistant break glass design
- LED alarm indicator
- Resettable element
- Plug and play terminal connections for fast wiring
- Allows wiring continuity testing before fitting
- Built-in loop isolator
- Easy to test with auto reset
- Fast (3s) response

DMN960IE

990 Series Manual Call Point Waterproof With Isolator - Red (Surface Mount)

Spécifications techniques

Général

Indication d'état	Red LED (Alarm), Yellow LED (Isolated)

Électrique

Operating voltage	17 to 28 VDC
Tension de communication	5 to 9 V (Protocol)
Consommation de courant	4 mA (Alarm (LED on) 1 mA (Power-up surge, 1 s) 100 µA (Quiescent)

Caractéristiques physiques

Dimensions physiques	93 x 98 x 71 mm (L x W x H)
Net weight	240 g
Couleur	Rouge
Entrées de câble	M20
Matériel (contacts)	Polycarbonate / ABS

Environnement

Operating temperature	-30 to +70°C (no icing)
Relative humidity	0 to 95% noncondensing
Environnement	Extérieur
IP rating	IP67

Régulateur

Certification	EN54-11, EN54-17

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 February 2025 - 11:37