DT657

Détecteur de chaleur, 90°C CS

General

The 650 Series conventional detectors are designed for the highest effectiveness utilising the latest technology. A wide operating voltage (9 to 33 VDC) allows them to be used on any security system.

Ionisation Detectors

The detector sensor consists of 2 cambers - an open outer chamber and a semi-sealed reference chamber. As smoke enters the open chamber, the voltage difference between the chambers is measured and compared to a pre-set trigger level for alarm. An integrating ionisation detector, suitable for use in areas where transient levels of smoke may be present, is also available.

Optical Smoke Detectors

These detectors use a pulsing LED and photo diode in an dark optical chamber. In the event of smoke from a fire entering the chamber, the light from the LED is scattered and registered by the photo diode.

Series 650 Heat Detectors

Heat detectors normally use a matched pair of thermistors (one exposed and one sealed) to sense heat. In case of fire, the exposed thermistor's temperture increases rapidly, causing the detector to change into the alarm state becuase of the imbalance. Rate-of-rise algorythms may detect the fire as the temperature increases, but a fixed upper temperture limit will force the detector into alarm if the rate of temperature increase has been too slow. The static only response heat detectors use only one thermistor and changes to the alarm state at a preset temperature.

Standard Base

The base enables detectors to be plugged in without any need for force - particularly useful when fitting to suspended ceilings. The base has a "one way only" fit and are lockable. They contain no electronic parts that could be damaged during installation. The detectors are polarity insensitive and bases are easy to wire with an earth connector.



Détails

- Advanced electronic technology
- Flashing LED option on selected units
- Polarity insensitive
- Common base
- Elegant slim-line design
- EN54 approved
- Proven detection performance
- May be used on security systems
- Wide range of bases available

DT657
Détecteur de chaleur, 90°C CS

Spécifications techniques

Général

Indication d'état	Red alarm LED

Électrique

Operating voltage	9 to 33 VDC
Consommation de courant	52 mA @ 24 VDC (Alarm) 17 mA @ 9 VDC (Alarm) 45 µA @ 24 VDC (Quiescent) 40 µA @ 9 VDC (Quiescent)

Sortie

Sortie d'alarme à distance	17 mA

Caractéristiques physiques

Dimensions physiques	100 x 45 mm (Ø x H)
Couleur	Blanc
Type de montage	Assemblage sur socle

Environnement

Operating temperature	-20 to +90°C (no icing)
Relative humidity	0 to 95% noncondensing
Environnement	Intérieur
IP rating	IP54

Régulateur

Certification	EN54-5

Environmental

Max. wind	Not affected

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 14 March 2025 - 12:47