FC-172-001

Fusion Wireless Sounder (White)

General

The FC-172-001 is a WHITE, fire alarm sounder to be used with a wireless base. This 32 tone sounder is suitable for indoor use.

The sounder is quick and easy to install into the wireless base with a simple turn and lock mechanism.

The Range

The Fusion series consists of:

· Optical Smoke Detectors
· Multisensor Smoke Detectors
· A1R Heat Detectors
· CS Heat Detectors
· Sounders in red and white
· Combination Sounder VIDs and VADs
· Manual Call Points
· Interface Modules

Operating Principle

Wireless devices are often installed in buildings where wiring presents a challenge because the fabric of the building or its design is negatively affected by the use of cables. It could also be difficult to introduce cable runs into heritage buildings. It is for these architecturally sensitive buildings that the Fusion series was developed.

Every Fusion device is assigned an address from is base. This address is converted by the Fusion wireless loop interface to a device address similar to a wired device connected directly to the loop wiring.



Détails

- 32 selectable tones
- Integrated audio monitoring
- Volume control possible
- Third party EN approved
- Easy to install
- Proven technology

FC-172-001
Fusion Wireless Sounder (White)

Spécifications techniques

Général

Compatibilité	Wireless base FC-171-001

Électrique

Type de bloc d’alimentation	Batteries
Tension de fonctionnement	2.8 to 5 VDC

Sirène

Niveau de sortie	< 99 dB(A) @ 1 m (Tone dependant)
Level Adjustment (ajustement du niveau)	Analogue
Fréquence	Selectable
Tonalités sélectionnables	32
Nombre de phase	2

Caractéristiques physiques

Dimensions physiques	120 x 125 mm (Ø x H) - Including base
Poids net	650 g - Including base
Couleur	Blanc
Type de montage	Assemblage sur socle
Base de fixation	Sans fil

Environnement

Protégé contre le vandalisme	Non
Température de fonctionnement	-10°C to 55°C
Température de stockage	5°C to 30°C
Humidité relative	< 95% non-condensing
Environnement	Intérieur
Indice de protection	IP54

Régulateur

Conformité	CE, REACH, RoHS 2, WEEE
Certification	BOSEC, CPR
Normes	EN54-3 EN54-13

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 2 June 2026 - 12:21