FC-60-2010

Fusion Wireless Door Controller (White)

General

The FC-60-2010 is a white wireless door controller. It offer quick and easy to installation and connects via a Fusion or Ziton wireless gateway in the fire alarm system.

The door controller is able to hold heavy fire doors open, improving building ventilation. It automatically closes in the event of a fire.

Operation

The FC-60-2010 includes robust Fusion wireless operation, industry proven mechanics and the ability to individually test each device. Benefits don't stop there as it can also be included within phased evacuation plans via system cause and effects.

Reliability

The FC-60-2010 is third party EN certified and is compatible with the Fusion and Ziton systems via the EMS Fusion radio loop Module and Ziton wireless gateways.



Détails

- Combines proven mechanics with renowned wireless system operation
- Provides full health monitoring via system integration
- Can be included in phased evacuation plans via system cause and effect programming
- Third party EN approved

FC-60-2010
Fusion Wireless Door Controller (White)

Spécifications techniques

Général

Force de maintien kgf (kilogramme force)	7 kg
Release button	Non

Électrique

Power supply type	Batteries
Tension de fonctionnement	2.22 to 3.3 VDC
Consommation de courant	60 µA

Caractéristiques physiques

Physical dimensions	195 x 205 x 45 mm (W x H x D)
Poids net	0.5 kg
Couleur	Blanc
Entrées de câble	NA
largeur du vantail de porte Max	1600 mm
Test Max. de masse de la porte	160 kg
Essai de surcharge Max. de poids de chute	36 kg
Test Max. de frottement de la porte	0.8 Nm
Angle Min. entre la porte ouverte / la position fermée	66°

Environnement

Protection contre le vandalisme	Non
Température de fonctionnement	-10°C to 55°C
Température de stockage	5 to 30°C
Humidité relative	<95% noncondensing
Environnement	Intérieur

Régulateur

Conformité	CE, REACH, RED (2014/53/EU), RoHS 2, WEEE
Certification	BOSEC, CPR
Standards	EN54-25, EN 1155, BS7273-4 EN54-13

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 2 June 2026 - 12:29