FCX-178-001

Fusion Wireless Remote Indicator

General

The FCX-178-001 is a wireless remote indicator for use on the Fusion 868 MHz wireless fire alarm system.

Installation

The siting of field devices in confined or concealed spaces often results in the alarm indicator on the device moulding becoming obscured or hidden. In order to show the state of an alarm clearly when installed in areas such as ceiling or floor voids, the FCX-178-001 remote LED indicator can be programmed to indicate any alarm in the system and installed in any prominent position.

Product configuration

The FCX-178-001 has a high intensity red LED indicator positioned centrally on its white, round plastic moulding. The unit is designed to fit onto its wireless surface mounting base which also houses the batteries and the receiver/transmitter for the wireless interface. An easy to mount, first fix base is included where the orientation for wall mounting is clearly indicated, allowing the unit to always be installed in the correct orientation when wall mounted.



Détails

- High intensity red LED indication
- Compatible with the Fusion wireless fire alarm system
- Built-in locking mechanism preventing unauthorised removal
- Fully supervised including removal and battery status
- Fully programmable - may be linked to any single or combination of system alarms

FCX-178-001
Fusion Wireless Remote Indicator

Spécifications techniques

Général

Fréquence radio	868 MHz
Compatibilité	Fusion gateway FCX-532-001

Électrique

Type de bloc d’alimentation	Batteries
Batteries	6x AA Alkaline (Panasonic LR6AD Powerline / Varta 4006 Industrial)
Puissance de l'émetteur de sortie	Auto adjusting 0 - 14 dB (0 - 25 mW)

VID

Couleur	Red

Caractéristiques physiques

Dimensions physiques	113 x 81 mm (Ø x H)
Poids net	400 g
Couleur	Moulage blanc
Type de montage	Assemblage sur socle, Montage en surface
Position de montage	Ceiling, Wall
Base de fixation	Sans fil

Environnement

Protégé contre le vandalisme	Non
Température de fonctionnement	-10 to +50°C
Température de stockage	5°C to 30°C
Humidité relative	< 95% noncondensing
Environnement	Intérieur
Indice de protection	IP23

Régulateur

Conformité	CE, REACH, RoHS 2, WEEE
Certification	EN54-25

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 31 July 2025 - 16:49