

FE230

Door holder, surface mount, 400 N, with release button

General

The FE230 is a surface mount door holder, in a Bayblend housing, which offers a 400 N holding force and a release button. Cable entry is possible from the back or from the sides, and the release button can be located at the top, or one of the sides.

Magnet construction

The magnet is constructed with a pressed coil and anti-remnance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

For practical ease of installation, the door holder comes complete with electrical screw terminals.

The housing is predrilled in a practical, standard format for rapid mounting.

The door holder is supplied complete with a keeper plate, which offer angular adjustment.

The release button can be position in three different locations: top, left or right.

Cable entry can be done in four different locations: back, top, left or right.

Approvals

The FE230 is fully approved according to EN1155.



Détails

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Keeper plate included

FE230

Door holder, surface mount, 400 N, with release button

Spécifications techniques

Général

Force de maintien N (Newton) 400

Bouton de relâche Oui

Diode de suppression d'étincelles Yes

Protection de polarité inversée Yes

Électrique

Type de bloc d'alimentation 24 VDC

Consommation électrique 1.6 W

Cycle de service 100%

Caractéristiques physiques

Dimensions physiques 85 x 110 x 38 mm (W x H x D)

Environnement

Indice de protection IP54 (magnet)
IP42 (connection)

Régulateur

Normes EN1155

Produits compatibles

| Catégorie | Référence | Description |
|-----------------------|-----------|---|
| Ventouses de maintien | FE225-150 | Universal Bracket Wall or Floor Mounting - 150 mm |
| Ventouses de maintien | FE225-300 | Universal Bracket Wall or Floor Mounting - 300 mm |
| Ventouses de maintien | FE290 | Door Holder, Surface Mount, 400N, Mains Powered |
| Ventouses de maintien | FE527 | Standard Anchorplate for FE500 Series Magnets |
| Ventouses de maintien | FE529 | Swivel Anchorplate for FE500 Series Doormagnets |



En tant que société d'innovation, Carrier Fire & Security se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 27 February 2024 - 10:57