FF746N

16511 Dual IR Flame Detector In Eexd - IIC T6 Flame Proof Housing

General

The FF746N is a IR² flame detector in a flame proof housing. IR² models have excellent response to flame while providing immunity to extraneous sources. New micro-processor technology makes the detectors independent of flame intensity enabling it to operate through smoke, a layer of oil, dust, or water vapor. A high and low sensitivity setting according to EN54-10 is provided.

Successor of FF746

Installer and maintenance friendly

The units can be wired as conventional 2 wire, 4-20 mA, or relay contacts (fire, fault and pre alarm) in latching or non-latching operation. Remote test inputs are available to activate self-test.

A stainless steel adjustable bracket and weather shield is also available.

The units are tolerant to vibration, and wind does not affect the performance. The IR² unit has excellent tolerance to detector window contamination and can detect flame through glass windows.

A flame sensor test unit is available for accurate testing of the detectors.

Reducing false alarms

Most IR flame sensors respond to 4.3µm light, emitted by hydrocarbon flames. By responding to 1.0 to 2.7µm light emitted by every fire, all flickering flames can be detected. Gas fires not visible to the naked eye e.g. hydrogen may also be detected.

The IR² detectors, responding to adjacent IR wavelengths, enable it to discriminate between flames and spurious sources of IR radiation.

The combination of filters and signal processing allows the sensor to be used without risk of false alarms in difficult situations characterised by factors such as flickering sunlight.



Détails

- Dual IR detector
- High specification units for critical applications
- IP66 Housing
- Flame proof housing
- Low current consumption
- 2 Wire, 4 - 20 mA and relay operation
- Latching and non latching operation
- High / Low sensitivity setting
- Tolerance to detector window contamination
- Remote self test facility
- Microprocessor controlled
- Immunity to false sources (arc welding, lightning and static)
- Conforms to EN54: Part 10

FF746N

16511 Dual IR Flame Detector In Eexd - IIC T6 Flame Proof Housing

Spécifications techniques

Électrique

Tension de fonctionnement	14 to 30 VDC

Caractéristiques physiques

Poids net	2.5 kg

Environnement

Température de fonctionnement	-10 to +55°C
Storage temperature	-20 to +65°C
Humidité relative	95% max. noncondensing
Environment	Exd, Intérieur
Indice de protection	IP66

Supply voltage

	14 - 30 VDC

Supply current

	3/9, 4/8/14, 4-20, 8-20 mA

Relay contact ratings

	1 A @ 30 VDC (resistive load)

Field of view

	90° min. cone

Spectral response (IR)

	1 to 2.7 µm

Operating temperature

	-10°C to 55°C

Storage temperature

	-20°C to 65°C

Relative humidity

	95% non-condensing

IP Rating

	IP66

Weight

	2.5 kg

IEC marking

	EEx d IIC T6

EDWARDS
Built for Resilience

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 6 December 2024 - 8:54