GS301

Piezo glassbreak detector 6 m

High Performance

The glassbreak detector GS301 is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm. Suitable for use on standard window glass or plate glass the GS301 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 6m cable. They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



Détails

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

GS301

Piezo glassbreak detector 6 m

Spécifications techniques

Général

Technologie	Piezo
Types de bris de verre	Plaque
Gamme	6 m radius
Bouton anti-sabotage	Non

Filaire / sans fil

Filaire / sans fil	Câblés

Électrique

Valeur de l'alimentation	3 to 16 VDC
Consommation de courant	9 mA at 12 VDC 4 mA at 6 VDC

Caractéristiques physiques

Dimensions physiques	37 × 19 × 12 mm
Poids net	50 g
Couleur	Blanc
Type de montage	Montage en surface

Environnement

Température de fonctionnement	-25 to +70°C
Indice de protection	IP67

Régulateur

Certification	EN50131 Grade 2, VdS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:24