GS620N

Stand-alone shock sensor

Stand-alone shock sensor

The GS620N shock sensor offers a versatile solution for detection of forced entry through windows or doors. It can be mounted throughout a 360° axis, vertically and horizontally, by ensuring that the brand logo is readable from left to right.

The GS620N is a latching and LED indicating stand-alone shock sensor which includes adjustable gross attack and pulse count sensitivity. It also features first-to-alarm and second-to-alarm LED indication and provides a selectable walk-test facility.

Superior detection

Its unique design enables the shock sensor to discriminate between a real break-in attempt and everyday background noise by measuring the shock frequency caused by the displacement in the protected structure.

The sensor is designed to activate (contact will open) when an acceleration greater than 1 G is detected. This could be caused, for example by a strong blow, a high speed drill or sawing because the frequencies of these shocks fall within the sensors range of detection.

Adjustable sensitivity

The analysing capability has two separate detection criteria: gross attack and pulse count. The gross attack threshold is designed to react to a single blow, while pulse count alarms when a pre-selected number of smaller shocks, occuring within a 30 second timing interval is reached. Both detection levels can be adjusted so that the installlation can be fine tuned to the environment and fully tested using the walk test facility. This digital signal processing is designed to eliminate false alarms and assure reliable detection of all types of attacks.



Détails

- Reliable 24 hour loop perimeter protection
- Superior technology provides excellent detection and false alarm immunity
- Suitable for all types of solid structures
- Versatile mounting through 360° axis
- 24 carat gold plated internal mechanics for optimum performance & long life
- Integrated analyser
- Adjustable sensitivity for fine tuning installations
- LED indication

GS620N
Stand-alone shock sensor

Spécifications techniques

Général

Type de produit	Analyseur de choc
Contact d’alarme	28 VDC, 100 mA
Contact d'autoprotection	28 VDC, 100 mA
Bouton anti-sabotage	Oui

Détection

Gamme	Up to 6 m

Filaire / sans fil

Filaire / sans fil	Câblés

Électrique

Tension de fonctionnement	8 to 15 VDC
Consommation de courant	8 mA (quiescent) 2.5 mA (LED off)

Caractéristiques physiques

Dimensions physiques	93 × 30 × 25 mm
Couleur	Blanc

Environnement

Température de fonctionnement	-20 to +50°C

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:26