IM1640PAG-G3

Surface Mount Contact, Armored Cable, EN Grade 3 & NFA2P 3 shields

Commercial Surface Mount Contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Détails

- Designed for use in harsh environments
- Tamper loop
- Version with armored cable

IM1640PAG-G3

Surface Mount Contact, Armored Cable, EN Grade 3 & NFA2P 3 shields

Spécifications techniques

Général

Application type	Montage en surface
Contact type	NC
Connectivity	4 wires, 2 meters (armored cable)

Filaire / sans fil

Wired-wireless	Câblés
Operating gap	15 mm

Électrique

Longueur de câble	2 m
Tension	max. 40 VDC
Courant de commutation	max. 500 mA

Caractéristiques physiques

Dimensions physiques	58 x 22 x 12 mm (W x H x D)
Dimensions magnet	8 x 30 mm
Dimensions contact / sensor	8 x 30 mm
Colour	Blanc
Material	ABS

Environnement

Température de fonctionnement	-40° to +70° C
Indice de protection	IP67

Régulateur

EN50131 grade	Grade 3
Conformité	CE
Certification	NFA2P

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 5 June 2026 - 12:25