IO950NI

Apollo IO Unit (SA4700-102)

General

IO950NI is the new input/output unit which provides supervision of one or more normally open contacts connected to a single pair of cables and a set of changeover relay output contacts.

Mechanical Construction

The IO950NI is available in the new faceplate style enclosure. It is designed to be surface mounted to the wall and consists of 3 parts:
- a back box with knock-outs for cable entry
- a PCB assembly
- a protective front cover

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Détails

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Supervise one or more NO switches on a single cable pair
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO950NI
Apollo IO Unit (SA4700-102)

Spécifications techniques

Électrique

Tension de fonctionnement	17 to 35 VDC
Consommation de courant	0.9 mA (Power-up surge) 0.5 mA (Quiescent) 0.5 mA max. (LEDs disabled) 3.5 mA max. (Alarm LEDs On)

Caractéristiques physiques

Dimensions physiques	150 x 90 x 60 mm
Poids net	244 g

Environnement

Température de fonctionnement	-40 to +70°C
Humidité relative	0 to 95% noncondensing
Environnement	Intérieur

Régulateur

Certification	CPR, EN54-17, EN54-18

Electrical

Protocol voltage	5 t o 13 V peak-to-peak

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 13 August 2024 - 8:02