IO954N

Apollo Mains Switching IO Unit (SA4700-103)

General

IO954N is the new mains switching input/output unit which contains one or more normally open contacts connected to a single pair of cables. It also provides a voltage free change over relay output capable of switching mains.

Mechanical Construction

The IO954N is available in the new faceplate style enclosure. It is designed to be surface mounted to the wall and consists of 3 parts:
- a back box with knock-outs for cable entry
- a PCB assembly
- a protective front cover

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Détails

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Contains one or more NO contacts connected on a single pair of cables
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO954N
Apollo Mains Switching IO Unit (SA4700-103)

Spécifications techniques

Électrique

Tension de fonctionnement	17 to 35 VDC 5 to 13 V peak to peak (Protocol voltage)
Consommation de courant	1.1 mA (Power-up surge) 0.7 mA (Quiescent) 0.7 mA max. (LEDs disabled) 5.2 mA max. (Alarm LEDs On)

Caractéristiques physiques

Dimensions physiques	150 x 90 x 60 mm
Poids net	301 g

Environnement

Température de fonctionnement	-40 to +70°C
Humidité relative	0 to 95% noncondensing
Environnement	Intérieur

Régulateur

Certification	CPR, EN54-17, EN54-18

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 13 August 2024 - 8:02