KE-DB3010W

Excellence series intelligent device accessory - standard base

General

The innovative Excellence range of intelligent addressable devices offers advanced features for reliability and peace of mind. Coupled with features for ease of installation and maintenance on new fire detection systems, it's a perfect match for exceptional overall performance.

The KE-DB3010W is an Excellence series, traffic white surface mount first-fix base allowing any Kidde Excellence addressable devices to be inserted, removed or replaced without rewiring using an easy twist and lock action. An optical "floating" visual illusion blends the Excellence series detector into any environment beautifully.

The KE-DB3010W is supplied with a labeling tag that may be inserted at two locations around the base. Larger tags may also be ordered separately.

Ease of Installation

Forming an integral part of the device assembly, this standard base is provided with key-hole slots for screw fixing directly to ceiling structures or conduit boxes. Large rear cable entry and cable entry from the side allows for flexible and easy wiring to the base.

For special applications a multitude of base accessories are available for recess and surface installations, ensuring easy and practical installations.

Ease of Wiring & Testing

Clearly marked and colour coded terminals with captive screws ensure correct and secure wiring termination for loop connections and optional cable screening. Remote indicator support is available.

As Excellence series devices support integrated isolators on-board, provision is made in the base for bridging isolation cable breaks when a detector is not fitted. This allows pre-installation cable continuity testing and maintains continuity when a detector is removed from its base.

Ease of Use

Inserting the Excellence series device into the base is simplified by indications on the base showing the insert and lock positions, and by visual, haptic and audible feedback. To prevent unauthorised removal of a device from its base, an easy-to-active locking mechanism is incorporated into all devices. If activated, a device can only be released from its base using a dedicated tool.



Détails

- Includes an address tag for device labeling
- Dual address tag locations avoids base alignment to make tags visible
- A selectable detector locking mechanism protects against unauthorised removal
- Large rear cable entry with ample space for cables
- Side cable entry and exit possibilities without additional fixture requirements
- Flexible installation fixture with first fix screw features reduce installation time and effort
- Colour coded screen terminal for easy identification
- Clearly visible terminal marking avoids incorrect cabling
- Cable cut-length template in the base
- Robust, wire ready wiring terminals with captive clamping washers for quick installation
- Isolation bridges included allows loop measurements without devices installed
- Detector insert location and locked position indications facilitates visual cueing of the device, saving time and adding surety
- Simple twist-and-lock detector action with clip action audible feedback ensures the detector is properly inserted
- Dual contact points on every connector for reliable detector/base contact

KE-DB3010W

Excellence series intelligent device accessory - standard base

Spécifications techniques

Général

Compatibilité	Kidde Commercial Excellence series point detectors
Connectivité	2-wire loop, earth & remote indicator

Électrique

Cable specification	1 to 2.5 mm Ø / 0.8 to 5.2 mm² / AWG 18 to 10
Nbre de fils conducteur	2
Bornes	7 (A+, A-, B+, B-, Screen, RI+, RI-)

Caractéristiques physiques

Dimensions physiques	100 x 17 mm (Ø x H)
Poids net	55 g
Couleur	Blanc (RAL 9016)
Type de montage	Montage au plafond
Entrées de câble	5 side, 1 rear
Matériel (boîte)	Polycarbonate

Environnement

Protégé contre le vandalisme	Non
Température de fonctionnement	−10 to +65°C
Température de stockage	−30 to +75°C
Humidité relative	10 to 93% noncondensing
Environnement	Intérieur

Régulateur


Conformité	CE, REACH, RoHS 3, WEEE
Certification	CE

Produits compatibles

Catégorie	Référence	Description
Module de détection	KE-DBA-CAPW	ActivSense™ Intelligent Universal Base Accessory - Cap (White)
Module de détection	KE-DBA-LABW-L1S	
Module de détection	KE-DBA-LABW-L2S	
Module de détection	KE-DBA-LABW-L3S	
Module de détection	KE-DBA-LABW-L4S	
Module de détection	KE-DBA-LABW-S	
Module de détection	KE-DP3020W	
Module de détection	KE-DP3021W	
Module de détection	KE-DP3120W	
Module de détection	KE-DP3120W-SN	

Produits compatibles

Catégorie	Référence	Description
Module de détection	KE-DP3120W-SNV	
Module de détection	KE-DP3121W	
Module de détection	KE-DP3121W-SN	
Module de détection	KE-DP3121W-SNV	
Module de détection	KE-DT3001W-HAB	
Module de détection	KE-DT3101W-HAB	
Module de notification	AI673	Indicateur d'action lumineux et sonore
Module de notification	PA25/3L	PA25 Series Remote Indicator



KIDDE COMMERCIAL

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 25 June 2026 - 8:44