KE-IO3101-M

Excellence series intelligent addressable mains switching output unit with isolator

General

The innovative Excellence series of intelligent addressable devices offers advanced features for reliability and peace of mind. Coupled with features for ease of installation and maintenance on new fire detection systems, it's a perfect match for exceptional overall performance.

The Excellence series input/output devices are designed to provide much needed flexibility to input monitoring and output switching. These modules, combined with the powerful features of a Kidde Excellence series addressable CIE, give customers versatility for diverse applications.

The KE-IO3101-M is an Excellence series addressable mains relay unit with integrated short circuit loop isolation. Powered directly from the Excellence loop, it offers double pole, potential free, change-over relay contacts.

Applications


The KE-IO3101-M is designed for controlling the main electrical supply of ancillary, mains powered equipment. The unit is ideal for the control of extract fans and dampers. The relay may be programmed to be activated by any single device, groups of devices or all system devices. All types of system input signals can be arranged to operate the KE-IO3101-M which can include control panel indicators, zonal outputs, call points or detectors. Both normally closed and normally open relay connections are provided, which if wired incorrectly, can simply be reconfigured in the programming of the unit.

The KE-IO3101-M may be located anywhere on the Kidde Excellence loop where it occupies only 1 of 128 available addresses. Housed in a low profile molding, the interface is designed to clip directly onto a standard DIN rail fixing or be installed in a suitable wall mount housing. It is intended for installation for installation inside the equipment to be switched, thereby offering savings in installation costs

Installation & Maintenance Features

The KE-IO3101-M is connected to the CIE via a 2-wire communication loop that carries both power and control data. Tri-Colour LED indicators positioned on the front face of the unit provide the engineer with clear identification of the operational state of the unit, as well as the status of any input and/or output control. Additional manual test facilities on the unit allows local testing without the need for control panel intervention, saving time during installation and commissioning.

Excellence series devices use an advanced digital data communications protocol with extensive error correction algorithms to ensure system reliability.



Détails

- Loop powered, saving external supply and installation cost
- Provides an addressable, mains rated output with double pole, potential free change over contacts
- Normally Open / Normally Closed programmable for full installation flexibility
- Freely programmable to operate from any combination of input triggers
- DIN or wall mounted
- Local test features for ease of validation
- Local, clear operation status indication for ease of use

KE-IO3101-M

Excellence series intelligent addressable mains switching output unit with isolator

Spécifications techniques

Général

Indication d'état	Tri-coloured LEDs
Compatibilité	Kidde Commercial Excellence Systems
Méthode d'adressage	DIP Switches
Plage d’adresses	1 to 128

Électrique

Type de bloc d’alimentation	Alimenté en boucle
Tension de fonctionnement	17 to 29 VDC
Consommation de courant	300 µA @ 24 VDC (quiescent) 2.5 mA @ 24 VDC (active)
Tension de communication	4 to 11 V (pulsed)

Sortie

Quantité des sorties	1 x Dual
Type de sortie et classe	Double pole, change over - 1 A @ 60 VDC / 5 A @ 250 VAC (resistive load)

Isolation

Type	Negative line break
Isolement boucle de masse	2.5 mA (active)
Types de résistance	<0.08 Ω
Interrupteur de courant	1.05 A (continuous) / 1.4 A (short)
Courant de fuite	<1 mA
Tension d’isolation	14 to 15.5 VDC
Reconnecter la tension	14 to 15.5 VDC
Impedance requirements	≤ 32 devices between isolators
Quantity per loop	128

Caractéristiques physiques

Dimensions physiques	109 × 88 × 40 mm (W x H x D)
Poids net	220 g
Couleur	Signal blanc (RAL 9003)
Type de montage	Rail DIN, Montage en surface, Fixation murale
Matériel	PC / ABS
Spécification du câble	Loop: 0.13 to 3.31 mm² (12 to 26 AWG) shielded/unshielded twisted-pair < 52 Ω , < 500 nF

Environnement

Protégé contre le vandalisme	No
Température de fonctionnement	-22 to +55°C
Température de stockage	-30 to +65°C
Humidité relative	10 to 93% noncondensing
Environnement	Intérieur
Indice de protection	IP30

Régulateur

Conformité	CE, REACH, RoHS 3, WEEE
Certification	CPR
Normes	EN54-17, EN54-18

Output

Cable specification	0.13 to 3.31 mm² (12 to 26 AWG) shielded/unshielded twisted-pair

Produits compatibles

Catégorie	Référence	Description
Boîtiers	N-IO-MBX-1	
Boîtiers	N-IO-MBX-2	
Module d'interface	N-IO-SBX-2G	

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 11 August 2026 - 14:34