KE-IO3144

Excellence series intelligent addressable 4 input / 4 output unit with isolator

General

The innovative Excellence series of intelligent addressable devices offers advanced features for reliability and peace of mind. Coupled with features for ease of installation and maintenance on new fire detection systems, it's a perfect match for exceptional overall performance.

The Excellence series input/output devices are designed to provide much needed flexibility to input monitoring and output switching. These modules, combined with the powerful features of a Kidde Excellence series addressable CIE, give customers versatility for diverse applications.

The KE-IO3144 an Excellence series addressable 4 input/4 output unit with integrated short circuit loop isolation. Powered directly from the Excellence loop, it offers 4 inputs with selectable line supervision and 4 magnetically latched relay outputs.



Applications

The KE-IO3144 is designed to monitor any potential free contacts, and independently switch outputs for control of equipment. Any normally open or normally closed contact may be selected to be supervised or unsupervised. Normal, open, passive, active or short circuit states on the input are reported back to the CIE where, depending on the programming, separate actions may be taken for any of these states. Every output is a magnetically latched relay providing a potential free change-over contact. The output relays do not require power in either the active or passive states, saving on overall loop loading.

The KE-IO3144 may be located anywhere on the Kidde Excellence loop where it occupies only 1 of 128 available addresses. Housed in a low profile molding, the interface is designed to clip directly onto a standard DIN rail fixing or be installed in a suitable wall mount housing.

Installation & Maintenance Features

The KE-IO3144 is connected to the CIE via a 2-wire communication loop that carries both power and control data. Tri-Colour LED indicators positioned on the front face of the unit provide the engineer with clear identification of the operational state of the unit, as well as the status of any input and/or output control. Additional manual test facilities on the unit allows local testing without the need for control panel intervention, saving time during installation and commissioning.

Excellence series devices use an advanced digital data communications protocol with extensive error correction algorithms to ensure system reliability.

Détails

- Loop powered, saving external supply and installation cost
- Provides 4 individually programmable, addressable inputs and outputs on a single address, saving address locations on the loop
- Fully supervised, bi-level inputs for pre-alarm and alarm supervision using a single input
- Normally Open / Normally Closed programmable for full installation flexibility
- Magnetic latched output relays to reduce loop loading
- Freely programmable to operate from any combination of input triggers
- Local test features for ease of validation
- Local, clear operation status indication for ease of maintenance

KE-IO3144

Excellence series intelligent addressable 4 input / 4 output unit with isolator

Spécifications techniques

Général

Indication d'état	Tri-coloured LEDs
Compatibilité	Kidde Commercial Excellence Systems
Méthode d'adressage	DIP Switches
Plage d’adresses	1 to 128

Électrique

Type de bloc d’alimentation	Alimenté en boucle
Tension de fonctionnement	17 to 29 VDC
Consommation de courant	2.5 mA @ 24 VDC (active) 350 µA @ 24 VDC (standby)
Tension de communication	4 to 11 V (pulsed)

Entrée

Quantité entrée	4
Type d'entrée et classe	Bi-level, Supervised
États d'entrée	Active, Fault, Normale, Open, Short
Résistance de pré-alarme	3 kΩ to 7 kΩ
Résistance d'alarme	0.3 kΩ to 3 kΩ
Résistance de terminaison	15 kΩ, ¼ W, 1%

Sortie

Quantité des sorties	4
Type de sortie et classe	Relay, 2A @ 30 VDC (resistive load)

Isolation

Type	Negative line break
Isolement boucle de masse	2.5 mA (active)
Types de résistance	<0.08 Ω
Interrupteur de courant	1.05 A (continuous) / 1.4 A (short)
Courant de fuite	<1 mA
Tension d’isolation	14 to 15.5 VDC
Reconnecter la tension	14 to 15.5 VDC
Impedance requirements	≤32 devices between isolators
Quantity per loop	128

Caractéristiques physiques

Dimensions physiques	148 x 102 x 27 mm (W x H x D)
Poids net	145 g
Couleur	Signal blanc (RAL 9003)
Type de montage	Rail DIN, Montage en surface, Fixation murale
Matériel	PC / ABS
Spécification du câble	Loop: 0.13 to 3.31 mm² (12 to 26 AWG) shielded/unshielded twisted-pair < 52 Ω , < 500 nF

Environnement

Protégé contre le vandalisme	No
Température de fonctionnement	-22 to +55°C
Température de stockage	-30 to +65°C
Humidité relative	10 to 93% noncondensing
Environnement	Intérieur
Indice de protection	IP30

Régulateur

Conformité	CE, REACH, RoHS 3, WEEE
Certification	CPR
Normes	EN54-17, EN54-18

Input

Cable specification	0.5 to 4.9 mm² (10 to 20 AWG) shielded/unshielded twisted-pair

Output

Cable specification	0.13 to 3.31 mm² (12 to 26 AWG) shielded/unshielded twisted-pair

Produits compatibles

Catégorie	Référence	Description
Boîtiers	N-IO-MBX-1	
Boîtiers	N-IO-MBX-2	
Module d'interface	N-IO-SBX-2G	

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 19 August 2026 - 16:00