# KM304

## Carbon Monoxide Control Panel for Car Parks - 4 Zones

The KM304 is a 4 Zone Carbon Monoxide (CO) detection control panel designed for applications where concentrations of CO may accumulate and needs to be controlled in order to protect lives. The panel is able to accommodate 4 supervised detection zone using KMD300 CO detectors.The panel is compliant with UNE 23-301-88, CE, WEEE and RoHS.




## Détails

- Elegant design
- 4 Supervised CO detection zone
- Easy to install and to use
- Language customisation using language inserts
- Clear and accurate display of CO levels per zone
- Up to 15 detectors per zone
- Fast response times
- Extraction and alarm outputs per zone
- Supervision of all CO detectors and zones
- Using surface mount technology with low current consumption
- Compatible with KMD300 CO detectors
- UNE 23300:1984, CE, WEEE and RoHS compliant
- External and internal power supply support

# KM304

## Carbon Monoxide Control Panel for Car Parks - 4 Zones

## Spécifications techniques

### Électrique

| | |
|---|---|
| Consommation électrique | 95 W max. |
| Tension de fonctionnement | 230 VAC±10% 50 Hz |

### Zone

| | |
|---|---|
| Quantité de dispositifs par zone | 15 max. |
| Cote de câble | 300 m max., 3 core 1.5 mm² |
| Zone input voltage | 10 to 20 VDC |
| Supply current | 1 A max. |
| CO Sensitivity | 0 to 300 ppm |

### Caractéristiques physiques

| | |
|---|---|
| Dimensions physiques | 420 x 336 x 118 mm (W x H x D) |
| Poids net | 4.65 kg |
| Type de montage | Montage en surface |
| Entrées de câble | 4 x 20 mm (Ø, top) |

### Environnement

| | |
|---|---|
| Température de fonctionnement | 0°C to +40°C |
| Température de stockage | -10°C to +70°C |
| Humidité relative | 10 to 95 % non condensing |

### Relay

| | |
|---|---|
| No. of relays per zone | 3 |
| Contact rating | 5 A at 30 VDC or 8 A at 250 VAC |
| Switching power | 150 W max. |

### Produits compatibles

| Catégorie | Référence | Description |
|---|---|---|
| Module de détection | KMD300 | |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 4 June 2025 - 15:28