PS48VDC100W-DIN

48VDC 100W POWER SUPPLY WITH DIN RAIL MOUNT

Overview

KGS Fire & Security's wide range of power supplies provide solutions for all the majority of various applications. Available in wall format with adaptors, KGS Fire & Security supplies can be used with all major power plugs. Solutions include both in wall and “power brick” configurations. Switching supplies include advanced technology and power savings, meeting Level V (5) International Efficiency in compliance with California Energy Commission, Energy Star and the EU Code of Conduct for external power supplies. Supplies can be mixed and matched to a variety of KGS Fire & Security products to meet installation requirements.



Détails

- CE approved
- UL approved
- CSA approved
- Compact power supplies for use with PoE Switches Media Converters
- Low voltage outputs
- Models for Europe and UK region
- In line power supply

PS48VDC100W-DIN

48VDC 100W POWER SUPPLY WITH DIN RAIL MOUNT

Spécifications techniques

Électrique

Entrée d'alimentation secteur	90 to 264 VAC

Sortie

Tension de sortie de l'alimentation	48 VDC
Puissance d'alimentation de sortie	2 A

Caractéristiques physiques

Dimensions physiques	55 x 90 x 100 mm
Poids net	420 g
Couleur	Blanc
Types de format	Montage rail DIN

Régulateur

Conformité	CE, REACH, RoHS 2, WEEE

Standards Conformance

EMC	CISPR 22 Class B
EMC	EN55022 Class B
EMC	EN61204-3 Class B
EMC	FCC parts 15 Class B
BSMI : EMS requirements	EN55024
BSMI : EMS requirements	IEC-61000-4-2
BSMI : EMS requirements	IEC-61000-4-3
BSMI : EMS requirements	IEC-61000-4-4
BSMI : EMS requirements	IEC-61000-4-5
BSMI : EMS requirements	IEC-61000-4-6
BSMI : EMS requirements	IEC-61000-4-8
BSMI : EMS requirements	IEC-61000-4-11

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 21 January 2026 - 19:55