RF-EV1012-K4

Wireless PIR 12m 433-80plus

One way transmitter

The sensor has a chip tuned wireless transmitter that communicates with a 80plus receiver as, for example, used in the ZeroWire control panel.
The learn-in process of the sensor is identical to the process used with legacy sensors.
Each sensor reports a unique ID code with each transmission.
The sensor also reports the battery and transmitter condition (supervisory signal) to the panel every 18 minutes.

Mirror power

The patented optical mirror technology gives the advantage of gliding focus, which creates a volumetric detection curtain from floor level up to installation height resulting in a sensor that never loses track of the object.
In these series we are using a dual element digital pyro generating two volumetric curtains for each of the nine curtain sets.

5D signal processing

The unique 5D signal processing technology will look for a match in shape, size, speed, duration and environment to decide on an alarm condition.
The result is a unique combination of high detection sensitivity with high false alarm immunity.

Ease and flexibility of installation

1.Easy opening and closing system.
2.Easy access when changing the batteries.
3.Easy access to mirror optics.
4.Tolerates wall angle deviation and different mounting heights.
5.Limited loss of coverage when objects are placed in the field of the PIR vision.
6.One mounting plate for all sensors in the series.

Other members of the family

This family includes motion sensors with variants in detection ranges and a Pet Immune variant.
The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.



Détails

- Proven mirror optics inside to get a dense coverage pattern
- Selectable coverage pattern using mirror masks
- Full under crawl detection
- "5D" signal processing for false alarm immunity
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 5-years battery life with 1 battery
- Holding several security approvals

RF-EV1012-K4

Wireless PIR 12m 433-80plus

Spécifications techniques

Général

Technologie	PIR
Type d'application	Fixation murale
Anti-masquage	Non
Insensible aux animaux	Non
Caméra	Non
Temps mise en route du détecteur	1 min

Détection

Plage de détection maximale	12 m
Sélection de la plage de détection	6 m or 12 m
Nbre de rideaux	9
Couverture (champ de vision)	86°
Plage de vitesse cible	0.3 m/s to 3.0 m/s

Filaire / sans fil

Filaire / sans fil	Sans fil
Fréquence radio	433 MHz LoNa
Gamme en champs libre	300 m

Électrique

Consommation de courant	22 µA avg., 50 mA max.
Batteries	1 x CR123 (3.0 V, 1300 mAh lithium)
Durée de vie de la batterie	5 years

Caractéristiques physiques


Dimensions physiques	130 x 69 x 53 mm (L x W x H)
Poids net	146 g (incl. 1 battery)
Hauteur de montage	1.8 to 3 m

Environnement

Température de fonctionnement	-10 to +55°C
Humidité relative	95% max. noncondensing
Environnement	Intérieur
Indice de protection	IP30 IK02

Régulateur

EN50131 Grade	Grade 2



En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:27