SH-21-0200-0001-99

SmartCell Dual Smoke/Heat Detector

Overview

The SmartCell Dual Smoke / Heat Detector is quick and easy to install and offers individual addressing at the Excellence Control Panel or Gateway.

Features include dual smoke and/or heat detection, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the Excellence wireless gateway.



Détails

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- Unique design
- Inbuilt locking mechanism

SH-21-0200-0001-99
SmartCell Dual Smoke/Heat Detector

Spécifications techniques

Général

Fréquence radio	868 MHz
Compatibility	Excellence Gateway

Électrique

Batteries	3 x 3.6 V lithium thionyl chloride batteries. Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)

Détection

Sensitivity	Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS), 72 °C rate of rise (BR)

Caractéristiques physiques

Physical dimensions	110 x 58 mm (Ø x D)
Net weight	0.2 kg
Colour	Blanc
Mounting type	Montage au plafond

Environnement

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Intérieur

Régulateur

Compliancy	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certification	CPR
Standards	EN54-5 EN54-7 EN54-13 EN54-25

Produits compatibles

Catégorie	Référence	Description
Batteries	SH-836-000	
Module d'interface	SH-14-3201-000 1-99	
Équipement de test	SH-21-BASE-010 0	

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 24 April 2026 - 17:40