

SMA-L-iCLASS

MA SIGMA Lite - iCLASS, Multi-factor Bio/Card, HID iCLASS, 500 users, IP65, CE

MA SIGMA Lite & MA SIGMA Lite Plus Series

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door mullions, turnstiles or server rack doors. With two designs (with touchscreen: MA SIGMA Lite Plus ; without touchscreen: MA SIGMA Lite) and multiple embedded card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoor and outdoor.

Embedded web server

The MA SIGMA Lite Series enables on-device enrollment, terminal configuration and transaction log retrieval thanks to the embedded web server. Moreover, it can be used with any device (PC, laptop, tablet, smartphone), any operating system (Windows, Android, iOS) or any web browser (Google Chrome, Mozilla Firefox, Safari and Internet Explorer).

Enhanced interactivity

Thanks to the 2.8" QVGA touchscreen on the MA SIGMA Lite Plus Series, you can benefit from an enhanced user experience. The MA SIGMA Lite Plus holds T&A in and out function keys, User ID/PIN/BioPin management and intuitive icons and live messages.

Compatible with existing installations

The MA SIGMA Lite Series can be used to upgrade an existing installation or to complement the installation with MorphoAccess® SIGMA (Lite) devices using the MorphoManager application or MIK SDK on a Morpho network or the SecureAdmin™ application or SecureSDK™ on a BioScript network.

Enhanced security features

The MA SIGMA Lite Series encompasses the latest and greatest anti-fraud features, such as: fake finger detection, duress finger, timed anti-pass back function and banned/authorized user lists.



Détails

- Leading fingerprint technology inside - 1:10,000 user identification in 1 second
- High capacity - 30,000 templates, 250,000 IDs in authorized user list, 1 million logs
- Advanced anti-fraud features
- Flexibility - Optional Prox, iCLASS or MIFARE/DESFire contactless card reader
- Tough design - IP65 rated and vandal resistant (IK08, SIGMA Lite only)

SMA-L-iCLASS

MA SIGMA Lite - iCLASS, Multi-factor Bio/Card, HID iCLASS, 500 users, IP65, CE

Spécifications techniques

Système

Distance max. entre le lecteur et la centrale	Ethernet: 100 m, RS485: 1219 m
RTE (demande de sortie)	No
CSN (numéro de série carte)	Yes
Modèle de données personnalisé	Yes
Nbre de LED	1

Technologie

Type de lecteur	Biométrique
Fréquence de transmission du fonctionnement du lecteur	13.56 MHz
Technologie supportée 13,56 MHz	iCLASS (CSN), iCLASS (custom data), iCLASS SEOS
Module SAM intégré	No

Biométrique

Type de biométrie	Empreinte digitale
Type de capteur biométrique	Optical

Interface et connexions

Interface	Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand
Type de connecteur	Réseau, Queue cochon
Longueur de la queue de cochon	40 cm

Type d'autoprotection

Levier d'arrêt inviolable	No
Ouverture d'autoprotection	Yes

Opération

Autonome	Yes
Code PIN clavier	No

Électrique

Type de bloc d'alimentation	VDC
Valeur de l'alimentation	12 to 24 VDC

Caractéristiques physiques

Poids net	280 g
Poids à l'expédition	325 g
Couleur	Noir
Matériel	Polycarbonate
Types de format	Surdimensionné
Type de montage	Montage en surface

Environnement

Protection contre le vandalisme	No
Température de stockage	-10 to +55°C

Régulateur

Conformité	CE, FCC, REACH, RoHS
------------	----------------------

