SOC-E-IS(WHT)

Intrinsically safe conventional smoke detector

Description

The SOC-E-IS(WHT) is a WHITE, optical smoke detector designed for use in hazardous areas. It incorporates a remote indicator output and a removable chamber for easy maintenance.

The SOC-E-IS is fully compatible with the majority of current conventional systems and incorporates a unique high performance optical smoke chamber removing the need to use ionisation detectors in the majority of applications.



Hazardous Area Classification

ATEX II 1G
II - Equipment group (Non-Mining)
1 - Equipment category (for Zone 0 or 20)
G - Type of explosive atmosphere (Gas, Vapours and Mist)

Cenelec Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)
Ex - Explosion protection symbol
ia - Protection concept (Intrinsically Safe)
IIC - Apparatus group (Gas)
T5 - Temperature classification (100°C)
Ga - Equipment protection level (Continuous)
Tamb - Ambient temperature range (-20 to +55°C)

BASEEFA Certificate number

Bassefa 19ATEX0143X

Détails

- Removable, high performance chamber
- Automatic sensitivity window verification (ASWV) - Drift compensation technology
- Remote indicator output
- Wide voltage range (9.5 to 30 VDC)
- Single fire LED with 360° viewing
- Low profile design with one piece outer cover
- ATEX Classification to: Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)
- Suitable for installation in areas at Category 1 (including all lower categories)
- Approved by LPCB and VdS

SOC-E-IS(WHT)

Intrinsically safe conventional smoke detector

Spécifications techniques

Général

Status indication	LED
Compatibility	Aritech, Kilsen & Ziton conventional zone interfaces using the YBN-R/4(IS) base
Connectivity	2-wire zone

Électrique

Type de bloc d’alimentation	Zone alimentée
Tension de fonctionnement	12 to 30 VDC
Current consumption	35 µA (quiescent) <40 mA (alarm) 120 µA (sensitivity warning) <20 mA (remote indicator)

Détection

Detection principle	Optical light scatter

Caractéristiques physiques

Dimensions physiques	100 x 48 mm (Ø x H)
Poids net	106 g
Colour	Blanc
Type de montage	Assemblage sur socle, Montage au plafond
Matériel (boîte)	ABS
Marquage fonctionnel	BASEEFA Rating

Environnement

Protégé contre le vandalisme	No
Température de fonctionnement	-10 to +50°C
Température de stockage	-30 to +60°C
Relative humidity	<95% noncondensing @ 40°C
Environnement	Intérieur, IS
Evaluation de l’environnement hazardeux	Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)
Indice de protection	IP42

Régulateur

Conformité	CE, REACH, RoHS 2
Certification	CENELEC/ATEX, LPCB, VdS
Normes	EN54:7 IECEx BAS 19.0122X

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 21 March 2025 - 8:06