ST801

High Temperature Heat Probe (Latched)

General

The ST801 and ST802 thermal probe high temperature heat detectors have been designed to protect prom hazards where high temperatures are produced at a specific point. The sensitive element (bulb) can be set at a distance of up to 1 meter from the connection box.

Applications

One of the most common applications for the ST800 is the detection of fires in the extractor cowls of industrial kitchens.

The high reliability of thermal probes make them ideal for controlling automatic fire extinguishing systems such as CO2, aerosols, etc.

For easy adaptation to any monitoring control panels, two ST800 models are available:

ST801


The ST801 is a high temperature thermal probe heat detector with a latching relay that maintains the alarm even after the hazard temperature has fallen or disappeared. It may be used as a conventional detector and connected to any of the zones of the fire control panels from Kilsen.

ST802

The ST802 does not use latching relays. It simply has a potential free relay output allowing for NO, COM and NC connections.

Warning

The ST800 should not be used to protect large areas. The housing of the unit has not been designed to withstand high temperatures.



Détails

- Completely metal
- Adjustable from 50 to 300 °C
- Back and side cable input
- Sensitive probe with 1 m of stainless steel capillary piping
- Resistant to heat, grease and humidity
- Easy installation
- Easy connection
- Easy maintenance
- Ideal for commercial areas

ST801
High Temperature Heat Probe (Latched)

Spécifications techniques

Électrique

Tension de fonctionnement	24 VDC
Consommation de courant	100 mA (Alarm)

Caractéristiques physiques

Dimensions physiques	140 x 100 x 70 mm
Poids net	800 g
Couleur	Gris (RAL 7032)

Environnement

Température de fonctionnement	50 to 300°C
Environnement	Intérieur

General

Alarm Monitoring	Two wires to conventional zone

Physical

Probe Dimentions	150 x 3 mm (l x Ø)
Capilliary pipe length	1 m

KIDDE COMMERCIAL

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 29 August 2025 - 9:13