STX2401-C

EN 54-4 Approved, 24 V 1 A + 0.3 A Intelligent Power Supply

The Product

The STX2401-C is a fully featured EN54-4 approved power supply ideal for use in fire system applications. It features intelligent battery charging, monitoring and signaling. Regulated 27.6 VDC output will source up to 1.2 A into the load as well as providing up to 0.3 A for charging the standby batteries.

Maximum battery life is assured through continuous active battery monitoring and 2 different charge levels: bulk (fast charge) and temperature compensated final float. Once fully charged the product operates in Eco power saving mode, whereby the batteries are charged for 4 hours in every 24 hour period while still being continuously monitored. Deep discharge protection prevents premature battery failure when operating from standby for extended periods.

Inside the unit, a diagnostic led with various flash patterns, ensure accurate diagnostics when the unit is in fault.


Installer friendly

A STX2401-C power supply is supplied in a self-contained, wall mount housing that can also house up to 7 Ah batteries (not included). The housing has a metal construction, and is white of color. The housing features a center keyhole on the back for initial fixing to the wall, which is supported by 4 additional mounting holes.

A potential-free contact is used to signal faults due to output failure, battery fault, charger fault or internal fault. A second potential-free contact signals the loss of mains power. These ensure any fault conditions are reported to the monitoring equipment, and that appropriate action is taken in the event of loss of mains power

The battery charging circuit is energised only when a battery is correctly connected and the battery voltage is greater than 14 V.

A green and a yellow LED that are visible when the box is closed, indicates mains present and faults. An orange diagnostics LED inside the unit, distinguish between various faults by way of various flash patterns. These ensure that the fault condition can be correctly identified on the spot and appropriate action take to rectify the cause.



Détails

- Approved to EN54-4 / CPR
- Self contained box houses up to 7 Ah batteries
- Deep battery discharge protection
- Mains & Fault LED indicators
- Fault diagnostics led, inside of unit
- 2 x Relay outputs: Fault & Mains Fault
- Temperature compensated charging
- Wide input voltage range
- EcoCharge technology which reduces current consumption
- Battery monitor - battery missing, low battery, short-circuit, reverse connection & circuit impedance error
- Electronic overload protection shuts down output until overload or short circuit is removed

STX2401-C

EN 54-4 Approved, 24 V 1 A + 0.3 A Intelligent Power Supply

Spécifications techniques

Électrique

Valeur de l'alimentation	110 to 240 VAC, 50 Hz to 60 Hz
Consommation de courant	<1 A maximum at full load

Sortie

Tension	24 VDC
Alimentation de sortie	1 A

Batterie de secours

Capacité	Up to 2 x 7 Ah (in housing)
En charge	Constant current charge to 80% in 24 h, Float charging to 100% in 48 h
Protection de décharge importante	Battery disconnect at 21 V
Seuil d'avertissement de batterie faible	23 V

Caractéristiques physiques

Dimensions physiques	275 x 330 x 80 mm
Poids net	3.3 kg (without batteries) 8 kg (including 7 Ah batteries)
Couleur	Blanc
Matériel	Acier

Environnement

Température de fonctionnement	-10 to +40°C
Température de stockage	-20 to +80°C
Humidité relative	75% noncondensing

Output

Voltage	27 to 28.3 VDC with mains
	20.3 to 26.0 VDC on battery standby
Ripple	100 mV max.
Continuous current output	
- With 2.1 Ah batteries	1.5 A non-charging / 1.2 A charging
- With 7 Ah batteries	1.5 A non-charging / 1.2 A charging
Fuse - load	1.6 A
Fuse - battery	1.6 A
Constant current charge	0.3 A

Local indicators

On the front of the unit	Green LED - power
	Yellow LED - fault
Inside the unit	Orange LED - fault diagnostics

Signalling output

Fault relay	100 mA @ 60 VDC N/C contacts
Mains fault relay	100 mA @ 60 VDC N/C contacts

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 26 January 2026 - 1:40