TESTIFIRE-ADAP

XTR2 Adaptor for aspiration and flat detectors

General

The TESTIFIRE-ADAP is a specialist adaptor to replace the standard membrane on a Testifire XTR2 test cup. It enables functional testing of aspirating smoke detection systems. It can also be used to test flat/flush detectors.



Détails

- Fits to Testifire XTR2 in place of standard membrane
- Allows placement around ASD pipe and alignment with sampling hole
- Also suitable for use with flat or flush mounted detectors

TESTIFIRE-ADAP

XTR2 Adaptor for aspiration and flat detectors

Spécifications techniques

Caractéristiques physiques

Couleur	Noir

Environnement

Protégé contre le vandalisme	Non
Température de fonctionnement	5 to 45°C (41 to 113°F)
Température de stockage	-10 to 50°C (14 to 122°F)
Humidité relative	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Régulateur

Conformité	CE, REACH, RoHS 3, WEEE

SKU info

Product brand	testifire

Produits compatibles

Catégorie	Référence	Description
Équipement de test	TESTIFIRE-XTR2	
Équipement de test	TESTIFIRE-XTR2-6M	
Équipement de test	TESTIFIRE-XTR2-HEAD	

EDWARDS
Built for Resilience

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 25 October 2024 - 13:46