TESTIFIRE-XTR2

All-in-one connected smoke/heat detector test kit

Powerful insights, automated test reports & records

The Testifire-XTR2 combines testing and reporting to deliver on compliance, giving service companies and building owners the insight and assurance they demand. The Testifire-XTR2 is designed to work with all detector brands and models, and with both addressable and conventional systems.

Test modes

The Testifire-XTR2 supports all-in-one smoke and heat testing including smoke only, heat or hi-heat only, combined and sequential smoke/heat as well as ASD test compatibility.

DT Connect App

Every Testifire-XTR includes a 6-month trial of DT Connect premium. When the 6-month trial period ends, a DT Connect subscription is needed to continue accessing the full range of features. The Testifire-XTR2 can also be used without subscription, albeit with limited features.

DT Connect alongside the Testifire-XTR2, allows advanced features to streamline the testing process, easily manage site assets and optimise reporting capability by automatically generating test reports.

DT Connect allows for:
• Minimising time spent on basic tasks
• Panel time logging to synchronise test and panel event timestamps *
• Test result capturing
• Asset identification *
• Panel reconciliation *
• Job summary
• Shareable reports *
* Premium DT Connect features

Product information

The Testifire-XTR2 kit includes:

1 x TESTIFIRE-XTR2-HEAD
1 x TESTIFIRE-BP Li-ion Battery
1 x TESTIFIRE-GEN Smoke Generator
1 x TESTIFIRE-CHAK Charger Kit
1 x TES3 Smoke Cartridge



Détails

- Rapid smoke generation saves waiting time
- 50% faster heat and hi-heat activation compared with the legacy TM010
- Sequential & combined test modes including hi-heat testing up to 100°C
- TFT-LCD full colour touch screen user interface
- Automatic LED torch in dark environments
- Automatic test result capture with detector LED recognition support
- Clearing mode to prevent re-alarms
- Robust and repairable
- Bluetooth enables communication to the DT Connect App with 6-month free PREMIUM support
- Optional subscription for premium features in the DT Connect app and Cloud Portal

TESTIFIRE-XTR2

All-in-one connected smoke/heat detector test kit

Spécifications techniques

Électrique

Type de bloc d’alimentation	Batteries
Tension de fonctionnement	10.8 V (35.1 wh / 3250 mAh)
Consommation de courant	< 0.5 A rms (smoke testing) 4 to 6 A rms (heat testing)

Caractéristiques physiques

Dimensions physiques	406 x 156 x 150 mm
Poids net	1.25 kg
Poids à l'expédition	2.39 kg
Couleur	Noir, GrisGris

Environnement

Protégé contre le vandalisme	Non
Température de fonctionnement	5 to 45°C (41 to 113°F) - Head unit 5 to 40°C (41 to 104°F) - Charger cradle
Température de stockage	-10 to 50°C (14 to 122°F)
Humidité relative	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Régulateur

Conformité	CE, REACH, RoHS 3, WEEE
Certification	CE

SKU info

Product brand	testifire

Test

Carbon Monoxide	No
Heat	Yes
Smoke	Yes

Electrical

Battery type	Lithium Ion
Charging	USB-C connection to charging cradle

Physical

Stimulus type	Cartridge

Produits compatibles

Catégorie	Référence	Description
Équipement de test	CB001	Canvas Carrying Bag for the Test and Service Equipment
Équipement de test	ET011	Tube d'extension en fibres de verre de 1,2 m
Équipement de test	FG010	Outil universel de dépose, sur châssis oscillant
Équipement de test	TES3-6PACK	
Équipement de test	TESTIFIRE-ADAP	

Produits compatibles

Catégorie	Référence	Description
Équipement de test	TESTIFIRE-MEM	
Équipement de test	TESTIFIRE-MEML	
Équipement de test	TESTIFIRE-SOP	
Équipement de test	TESTIFIRE-XTR2-6M	

EDWARDS
Built for Resilience

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 21 October 2024 - 10:29