TVE-DEC13

TruVision Decoder for 16 Full HD streams, 2 outputs (HDMI, BNC), 12 VDC

Overview

The TruVision Video Decoder TVE-DEC13 is the ideal solution to decode IP video streams and show them on an analog or digital video output. Based on an advanced DSP and stable embedded system design, the TruVision video decoder provides high-resolution decoding functionality for live view from TruVision IP cameras, encoders, DVRs and NVRs.

Strong performance

The TVE-DEC13 can decode streams up to 32 MP. The unit can decode up to a maximum of 16 Full HD streams at the same time in H.264 or H.265 compression. These decoded streams can be shown on one of two monitor outputs using the pre-defined layouts. The decoder can also use the two monitor outputs at the same time and create a small video wall.
The Scene feature lets the user create pre-defined layouts of streams that can be activated by a single click of a button.
Besides decoding streams from TruVision devices, the decoder can also decode ONVIF and RSTP streams.

Integration with TruVision Navigator software

The TVE-DEC13 has been integrated in the TruVision Navigator software (as of version 9.5). This feature lets the user create scenes containing video streams from cameras that have been added in the TruVision software.
This means that static video layouts can be displayed via the decoder without using PC resources for decoding.

Why TVE-DEC13?

The TVE-DEC13 is a powerful device that can show video streams on up to two monitors without the use of a PC.
The integration in TruVision Navigator helps to lower the PC load for decoding video.

Applications

For showing video streams on confrontation monitors in retail.
In guarding rooms as a video wall (2 monitors) in combination with TruVision Navigator software.
At (remote) guard desks or offices for site monitoring.



Détails

- Supports H.264/H.264+ and H.265/H.265+ compression
- Powerful decoding capability, up to 32 MP
- Can simultaneously decode up to a maximum of 16 video streams in Full HD
- Multiple video display outputs: You can decode different cameras on the HDMI and BNC output.
- Compatible with TruVision IP cameras, TruVision recorders and TruVision encoders (See manual for details)
- Supports decoding for ONVIF and RTSP streams
- Integrated in TruVision Navigator (version 9.5 and newer)

TVE-DEC13

TruVision Decoder for 16 Full HD streams, 2 outputs (HDMI, BNC), 12 VDC

Spécifications techniques

Général

Technologie	Décodeur (de l'IP vers l'analogique)

Entrées vidéo / audio

Vidéo standard	NTSC, PAL
Compression vidéo	H.264, H.264+, H.265, H.265+
Compression audio	AAC, G.711A, G.711U, G.722, G.726, MPEG2-L2
Entrées audio bidirectionnelles	2-ch, 3.5mm connector (2.0 Vp-p, 1 kΩ)

Sorties vidéo / audio

Sorties vidéo	BNC, HDMI
Affichage multi-écrans	Full screen, 1x2, 2x2, 1+5, 1+7, 3x3, 3x4, 4x4
Sorties audio	1-channel, RCA

Interfaces

Interface réseau	1, RJ45 10 M / 100 M / 1000 M Auto-Negotiate Ethernet Interface
Interface série	RS-232, RS-485

Électrique

Type de bloc d’alimentation	VDC
Valeur de l'alimentation	12 VDC
Consommation électrique	15 W
Consommation de courant	1.25 A

Caractéristiques physiques

Dimensions physiques	220 x 148 x 45 mm
Poids net	1663 g
Types de format	Bureau

Environnement

Température de fonctionnement	-10 to +55 C° 14 to 131 °F
Humidité relative	10 to 90% noncondensing

Régulateur

Conformité	CE, REACH, RoHS, WEEE

Video / audio inputs

Incoming bandwidth	70 Mbps

Video / audio outputs

HDMI	1 channel / 4K: 3840 x 2160 @30Hz 2560 x 1440 @30Hz 1920 x 1200 @60Hz 1080P: 1920 x1080 @50/60Hz WSXGA:1680 x 1050 @60Hz UXGA:1600 x 1200 @60Hz 720P:1280 x 720 @50Hz/60Hz SXGA:1280 x 1024 @60Hz XGA:1024 x 768 @60Hz
BNC	1 channel / 704 x 576

General

Video Decoding Channels	32 MP: 1 channel 24 MP: 1 channel 12 MP: 2 channels 8 MP (4K): 4 channels 6 MP: 5 channels 4 MP: 9 channels 2 MP and lower: 16 channels All resolutions at max. 25/30 fps

Supported products

Devices	See User Manual.

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 24 August 2026 - 18:04