TVPA-S02-0601-360-G

TruVision 360° IP camera, 6MP, 15m IR, audio, 360° fisheye lens, PoE-af, IK10, IP67

Product overview

Ideally suited for a variety of applications, the TruVision 360º network cameras provide high-quality image capture that delivers a complete view of indoor or outdoor areas for exceptional security coverage. The 6 and 12 MP indoor and outdoor models are very effective for applications where wide areas need to be covered, such as intersecting corridors, parking garages, counters and warehouses. The cameras can also be used in a wall-mount configuration to capture panoramic scenes. With an IR range of up to 15 m, they can also be used in low-light environments and for 24/7 exterior surveillance. Extra accessories are available for pendant and wall mount installation.

ImmerVision lens

The ImmerVision panomorph lens is superior to traditional panoramic lenses. It beats traditional wide-angle technology in performance and video coverage and allows users to navigate within the panoramic camera image without distortion. Panomorph technology is the most effective way to achieve more coverage, better image quality and compatibility.

Smart retail analytics

Embedded intelligence features like Heat Map, Queue Management , People Counting, and Intersection Analysis help retail owners to better understand the customer journey. It shows how customers move, how much time they spend in different zones and their in-store behaviour. This valuable data, which can also be exported or emailed periodically, gives an overview of the busiest and least busy times of day allowing retailers to optimize and allocate their staff accordingly.



Détails

- 6MP 1/8" progressive scan CMOS
- H.265(+) compression
- 360° ImmerVision panomorph lens
- 180° and 360° panoramic views
- Heat map, Queue mangement, People counting, and Intersection analysis
- Multiple fisheye + ePTZ combined viewing modes
- Up to 15 m IR range
- 2-way audio, built-in mic and speaker
- Built-in SD/SDHC card slot
- Ceiling, wall and desk mount options

TVPA-S02-0601-360-G

TruVision 360° IP camera, 6MP, 15m IR, audio, 360° fisheye lens, PoE-af, IK10, IP67

Spécifications techniques

Général

Technologie	IP
Vidéo standard	NTSC, PAL
OSD	Picture Overlay, Text Overlay
Masque de confidentialité	8 configurable masking zones
Logiciel compatible	Advisor Advanced Pro mobile app., Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile, Web Browser

Caméra

Taille de capteur	1/1.8"
Résolution maximum	6 MPX
Balayage de détection	Progressive
Type de capteur	CMOS
Durée d'obturation	1 to 1/100,000 s

Performance d'éclairage

Type de WDR	Digital WDR
Réduction du bruit numérique	3D DNR
Jour / nuit	True Day/Night
Filtre IR motorisé	Oui
Sensibilité couleur	0.01 Lux @ (F2.25, AGC ON)
Sensibilité N/B	0.005 Lux @ (F2.25, AGC ON), 0 Lux with IR on
Infrarouge (IR)	Oui
Portée IR	Up to 15 m; 3 LEDs
ongueur d'onde IR	850 nm

Encodage

Compression vidéo flux principal	H.264, H.264+, H.265, H.265+
Compression vidéo sous-flux	H.264, H.265, MJPEG
Taux d'échantillonnage video	32 to 16 Mbps
Résolution maximale @ips	2560 × 2560 @ 25/30 fps

Objectif

Type d'objectif	ImmerVision panomorph lens
Longueur de focale	1.16 mm, horizontal FoV 180°, vertical FoV 180°
f-stop	2.25

DORI

Detection	23.2 m
Observation	9.2 m
Recognition	4.6 m
Identification	2.3 m

Réseau

Interface réseau	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Intégration	CGI, ISAPI, ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protocoles réseau pris en charge	802.1x, Bonjour, DDNS, DHCP, DNS, DynDNS, ezDDNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, Qos, RTCP, RTP, RTSP, SMPTP, SNMP, SSL/TLS, TCP/IP, UDP, UPnP

Audio

Compression audio	AAC, G.711, G.711alaw, G.722.1, G.726, MP2L2, MP3, PCM
Entrée audio	4 built-in microphones and 1 input (line in), 3.5 mm connector, max. input amplitude: 3.3 Vpp, input impedance: 4.7 KΩ, interface type: non-equilibrium
Sortie audio	Built-in speaker and 1 output (line out), 3.5 mm connector, max. output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium
Taux d'échantillonnage audio	64 Kbps (G.711ulaw/G.711alaw), 16 Kbps (G.722.1), 16 Kbps (G.726), 32 to 192 Kbps (MP2L2), 8 to 320 Kbps (MP3), 16 to 64 Kbps (AAC-LC)

E/S d'alarme

Entrées d'alarme	2
Sorties d'alarme	2 (max. 24 VDC, 1A)

Stockage

Type de stockage local	Built-in micro SD/SDHC/SDXC slot
Max. SD card capacity	Built-in memory card slot, supporting microSD/microSDHC/microSDXC card up to 256 GB

Vidéo intelligence

ROI	4 regions for each stream
Smart event	Audio exception detection, Heat map, Intersection analysis, Intrusion detection, Détection de passage à niveau, Motion detection, Détection de suppression d'objet, People counting, Region entrance detection, Détection de région de sortie, Scene change detection, Unattended baggage detection

Électrique

Tension de fonctionnement	12 VDC ±20% PoE IEEE 802.3af, Class 3
Consommation électrique	12 VDC: 1 A, max. 11.5 W PoE: max. 12.5 W

TVPA-S02-0601-360-G

TruVision 360° IP camera, 6MP, 15m IR, audio, 360° fisheye lens, PoE-af, IK10, IP67

Caractéristiques physiques

Dimensions physiques	Ø 140.3 × 59.4 mm Ø 5.5 × 2.3 in.
Poids net	Approx. 715 g Approx. 1.58 lbs
Poids à l'expédition	Approx. 1206 g Approx. 2.66 lb.
Couleur	Gris (Pantone 428c)
Form Factor	360 degrés

Environnement

Evaluation de l'impact	IK10
Environnement	Extérieur
Température de fonctionnement	-40 to +60°C 40 to +140°F
Chauffage intérieur	Oui
Humidité relative	≤95% noncondensing
Indice de protection	IP67

Régulateur

Conformité	C-tick, CE, REACH, RoHS, WEEE

Network

Simultaneous live view	Up to 20 channels

Viewing modes

Nbr. of display modes	20
Software decoding	Fisheye view, 180 panorama view, 360 panorama view, 360 panorama + PTZ, 360 panorama + 3PTZ, 360 panorama + 6PTZ, 360 panorama + 8PTZ, 2PTZ, 4PTZ, fisheye + 3PTZ, fisheye + 8PTZ, hemisphere, AR hemisphere, cylinder.
Hardware decoding	Fisheye view, 180 panorama view, 180 dual channel panorama, panorama view, 4PTZ, fisheye + 3PTZ, 4PTZ fusion

Video intelligence

Intersection analysis	Detect and analyze flow in an intersection-like scene, and generate reports. Support one intersection with max. 10 ways.
Heat map	A graphical representation of visits (by calculating amount of people or amount of dwell time) in a configured area. Two report types, space heat map and time heat map line chart are supported.
Queue management	Supports up to 8 detection regions, and independent arming schedule and linkage method. Supports 2 detection modes: regional people queuing-up, waiting time detection. Generates reports to compare the efficiency of different queuing-ups and display the changing status of one queue. Supports real-time data uploading and scheduled data uploading. Regional people queuing-up: 4 alarm trigger conditions, including greater than threshold, less than threshold, equal to threshold, not equal to threshold. Waiting time detection: 1 alarm trigger condition, including greater than threshold.

Encoding

Main stream compression	Fisheye View: 2560 × 2560, 2048 × 2048, 1280 × 1280
	180 Panorama View: 2048 × 1536, 1920 × 1440
	180 Dual Channel Panorama View: 2048 × 768, 1920 × 720
	Panorama View: 2048 × 1536, 1920 × 1440
	4PTZ View: camera 01/camera 02/camera 03/camera 04: 1024 × 768
	Fisheye + 3PTZ View: camera 01: 2048 × 2048, 1024 × 1024, camera 02/camera 03/camera 04: 1024 × 768
	4PTZ Fusion View: 2048 × 1536, 1600 × 1200
Sub stream compression	Fisheye View: 720 × 720, 480 × 480
	180 Panorama View: 640 × 480, 320 × 240
	180 Dual Channel Panorama View: 640 × 480, 320 × 240
	Panorama View: 640 × 360, 320 × 240
	4PTZ View: camera 01/camera 02/camera 03/camera 04: 640 × 480, 320 × 240
	Fisheye + 3PTZ View: camera 01: 720 × 720 camera 02/camera 03/camera 04: 640 × 480, 320 × 240

Produits compatibles

Catégorie	Référence	Description
Fixations et Supports	TVPA-BB-01	
Fixations et Supports	TVPA-CB-01	

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 7 August 2026 - 14:12