TX-2214-03-1

Wireless PIR 16m 868AM Gen2

One way transmitter

The sensor has a chip tuned wireless transmitter that communicates with a 868AM Gen2 receiver as, for example the ATS1235.
The learn-in process of the sensor is identical to the process used with legacy sensors.
Each sensor reports a unique ID code with each transmission.
The sensor also reports the battery and transmitter condition (supervisory signal) to the panel every 18 minutes.

Mirror power

The patented optical mirror technology gives the advantage of gliding focus, which creates a volumetric detection curtain from floor level up to installation height resulting in a sensor that never loses track of the object.
In these series we are using a dual element digital pyro generating two volumetric curtains for each of the nine curtain sets.

5D signal processing

The unique 5D signal processing technology will look for a match in shape, size, speed, duration and environment to decide on an alarm condition.
The result is a unique combination of high detection sensitivity with high false alarm immunity.

Ease and flexibility of installation

1.Easy opening and closing system.
2.Easy access when changing the batteries.
3.Easy access to the mirror optics.
4.Tolerates wall angle deviation and different mounting heights.
5.Limited loss of coverage when objects are placed in the field of the PIR vision.
6. One mounting plate for all sensors in the series.

Other members of the family

This family includes motion sensors with variants in detection ranges and a Pet Immune variant.
The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.



Détails

- Proven mirror optics inside to get a dense coverage pattern
- Selectable coverage pattern using mirror masks
- Full under crawl detection
- "5D" signal processing for false alarm immunity
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 5-years battery life with 1 battery
- Holding several security approvals

TX-2214-03-1
Wireless PIR 16m 868AM Gen2

Spécifications techniques

Général

Technologie	PIR
Type d'application	Fixation murale
Anti-masquage	Non
Insensible aux animaux	Non
Caméra	Non
Kit levier d'arrêt anti-ouverture	On board
Temps mise en route du détecteur	1 min

Détection

Sélection de la plage de détection	10 or 16m
Nbre de rideaux	9
Couverture (champ de vision)	86°
Protection sous-jacente	Oui
Plage de vitesse cible	0.3 m/s to 3 m/s

Filaire / sans fil

Filaire / sans fil	Sans fil
Fréquence radio	868 MHz AM

Électrique

Consommation de courant	22 µA (avg.), 50 mA (max.)
Batteries	1 x CR123A (3.0 V, 1300 mAh lithium)
Durée de vie de la batterie	5 years

Caractéristiques physiques

Dimensions physiques	130 x 69 x 53
Poids net	146 g
Hauteur de montage	1.8 to 3 m

Environnement

Température de fonctionnement	-10° to +55° C
Humidité relative	95% max. noncondensing
Environnement	Intérieur
Indice de protection	IP30 IK02

Régulateur

EN50131 Grade	Grade 2
Certification	INCERT

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:27