

1078-N

Recessed magnetic contact for steel doors, white

Steel door applications

The Sentrol 1078(C/T) series steel door contacts are designed specifically for use in the steel doors commonly found in commercial building applications. Many models including, wide gap, SPDT and biased for high security applications make the 1078 series the most widely used and comprehensive line available.

Easy Installation

The unique housing design features a rugged body construction with flexible ribbed sides for quick, secure installation without gluing. The magnet housing isolates the magnet from the surrounding steel for maximum gap distances, both make and break.

Durability and dependability

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



Détails

- Special design for steel mounting
- Self-lock mounting
- Rugged construction
- Comprehensive product range

1078-N

Recessed magnetic contact for steel doors, white

Spécifications techniques

Général


Type d'application	Montage encastré
Type de contact	NC
Connectivité	30 cm wire leads

Filaire / sans fil

Filaire / sans fil	Câblés
Déficit de fonctionnement	13 mm (max.)

Caractéristiques physiques

Dimensions du capteur magnétique	25 x 40 mm (Ø x L)
Dimensions contact / capteur	25 x 29 mm (Ø x L)
Couleur	Blanc



En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web.fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 5 May 2023 - 9:53